

PV1470 - Cell data sheet

Classification

Brand Alcad
Cell type PV1470
Cell P/N 31-10037-8*
Capacity at 5 hours rate 1 350 Ah
IEC Designation KGL 1350 P



Physical data

According to IEC 62259

Overall height 405 mm

Width 195 mm Weight per cell 55,9 Kg

Length 425 mm Block length - 2 cells
Block length - 3 cells
Block length - 5 cells
Block length - 6 cells
Block length - 7 cells
Block length - 8 cells
Block length - 9 cells
Block length - 10 cells

Construction

Container materialPolypropyleneNo. of terminals/polarity5Separator typeFeltTerminal materialSteel

Connection torque 30,0 +/- 3,0 Nm Vent type flame arresting vent Terminal size M10 (large)

Plates

Positive Negative

Type of plates Ultra Low Maintenance Type of plates Ultra Low Maintenance
Pocket Pocket



PV1470 - Cell data sheet

Electrolyte

Electrolyte type: Renewal

Electrolyte type: Initial Electrolyte per cell: Liquid

E13 E29 Max/Min

Vent oil quantity

50 mm

Connection

Cable area

95 mm²

Charging

Float voltage Single-level voltage 1,42 V/Cell 1,42 V/Cell High rate voltage (min)

1,45 V/Cell

Resistance/Short circuit

Internal resistance

0,18 mOhm

Short circuit current

8176 A

Performance data

Photovoltaic performance

For a fully charged cell after a constant current charge according to IEC 62259 standard at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell

1h

1

1 901