



## PV1620 - Cell data sheet

### Classification

---

Brand	Alcad
Cell type	PV1620
Cell P/N	31-10040-8*
Capacity at 5 hours rate	1 500 Ah
IEC Designation	KGL 1500 P
According to IEC 62259	



### Physical data

---

Overall height	405 mm		
Width	195 mm	Weight per cell	62,8 Kg
Length	472 mm	Block length - 2 cells	
Block length - 3 cells		Block length - 4 cells	
Block length - 5 cells		Block length - 6 cells	
Block length - 7 cells		Block length - 8 cells	
Block length - 9 cells		Block length - 10 cells	

### Construction

---

Container material	Polypropylene	No. of terminals/polarity	6
Separator type	Felt	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	flame arresting vent
Terminal size	M10		(large)

### Plates

---

Positive		Negative	
Type of plates	Ultra Low Maintenance Pocket	Type of plates	Ultra Low Maintenance Pocket

ALCAD confidential and proprietary. The data herein given are for information purposes only and are not binding on ALCAD. They may be modified without prior notice. Please contact an ALCAD representative in order to obtain confirmation of the above data.

Visit our website at [www.alcad.com](http://www.alcad.com)

Version: 1.5, Last updated on 04/2015

P 1/2



## PV1620 - Cell data sheet

### Electrolyte

---

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E29	Vent oil quantity	
Electrolyte per cell: Liquid	15,6 liters		

### Connection

---

Cable area	95 mm <sup>2</sup>
------------	--------------------

### Charging

---

Float voltage	1,42 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,42 V/Cell		

### Resistance/Short circuit

---

Internal resistance	0,16 mOhm	Short circuit current	9085 A
---------------------	-----------	-----------------------	--------

### Performance data

---

#### Photovoltaic performance

For a fully charged cell after a constant current charge according to IEC 62259 standard at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	1h
1	2 113