




LBE1200P - Cell data sheet

Classification

Brand	Alcad
Cell type	LBE1200P
Cell P/N	310548281
Capacity at 5 hours rate	1.200 Ah
IEC Designation	KL1200P
According to IEC 60623	



Wiring principle



Crosswise

Physical data

Overall height	410 mm		
Cell height	400 mm		
Width	195 mm	Weight per cell	50,6 Kg
Length	390 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	5
Separator type	Grid	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	
Terminal size	M10 SW 16 mm		
		Handle	Yes

Plates

Positive		Negative	
Type of plates	Pocket	Type of plates	Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	13,3 liters		

Connection

Cable area of internal connection cables	70 mm ²	End-lug (and external cable)	50 mm ²
--	--------------------	------------------------------	--------------------



LBE1200P - Cell data sheet

Charging

Float voltage	1,42 V/Cell	High rate voltage (min)	1,47 V/Cell
Single-level voltage	1,43 V/Cell		

Resistance/Short circuit

Internal resistance	0,14 mOhm	Short circuit current	9983 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	124	153	240	384	512	617	790	1.019	1.143	1.228	1.319	1.513	1.680	1.800	2.160	2.322
1,05	123	152	237	372	464	530	661	862	953	988	1.098	1.253	1.351	1.477	1.774	1.925
1,1	120	147	226	313	393	453	534	671	725	795	876	919	1.101	1.200	1.461	1.602
1,14	117	138	199	271	325	361	416	531	569	590	664	772	897	981	1.221	1.351
1,16	110	126	172	233	278	300	341	447	497	537	589	704	818	895	1.113	1.233

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	143	175	268	411	536	638	808	1.029	1.150	1.232	1.322	1.513	1.680	1.800	2.160	2.322
1,05	143	176	270	410	503	570	705	912	1.005	1.041	1.154	1.316	1.419	1.550	1.863	2.022
1,1	140	171	261	354	441	505	593	741	800	876	964	1.011	1.211	1.320	1.607	1.762
1,14	138	162	232	314	375	414	476	607	649	674	757	880	1.023	1.118	1.392	1.541
1,16	129	148	202	272	324	350	397	519	577	623	683	817	950	1.038	1.292	1.430



LBE1200P - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,7	7,85	5,00	3,12	2,34	1,95	1,52	1,18	1,05	0,98	0,91	0,79	0,71	0,67	0,56	0,52
1,05	9,8	7,88	5,05	3,23	2,58	2,26	1,81	1,39	1,26	1,21	1,09	0,96	0,89	0,81	0,68	0,62
1,1	10,0	8,16	5,31	3,83	3,05	2,65	2,25	1,79	1,66	1,51	1,37	1,31	1,09	1,00	0,82	0,75
1,14	10,2	8,68	6,04	4,42	3,69	3,33	2,89	2,26	2,11	2,03	1,81	1,55	1,34	1,22	0,98	0,89
1,16	10,9	9,5	6,98	5,15	4,32	3,99	3,52	2,69	2,41	2,23	2,04	1,70	1,47	1,34	1,08	0,97

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,38	6,87	4,47	2,92	2,24	1,88	1,49	1,17	1,04	0,97	0,91	0,79	0,71	0,67	0,56	0,52
1,05	8,41	6,83	4,45	2,93	2,38	2,11	1,70	1,32	1,19	1,15	1,04	0,91	0,85	0,77	0,64	0,59
1,1	8,55	7,01	4,60	3,39	2,72	2,37	2,02	1,62	1,50	1,37	1,24	1,19	0,99	0,91	0,75	0,68
1,14	8,71	7,41	5,17	3,82	3,20	2,90	2,52	1,98	1,85	1,78	1,58	1,36	1,17	1,07	0,86	0,78
1,16	9,27	8,09	5,94	4,41	3,71	3,43	3,03	2,31	2,08	1,93	1,76	1,47	1,26	1,16	0,93	0,84