




LBE1400P - Cell data sheet

Classification

Brand	Alcad
Cell type	LBE1400P
Cell P/N	310548481
Capacity at 5 hours rate	1.400 Ah
IEC Designation	KL1400P
According to IEC 60623	



Wiring principle



Crosswise

Physical data

Overall height	410 mm	Weight per cell	58,2 Kg
Cell height	400 mm		
Width	195 mm		
Length	438 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	5
Separator type	Grid	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	
Terminal size	M10 SW 16 mm		
		Handle	Yes

Plates

Positive		Negative	
Type of plates	Pocket	Type of plates	Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	14,8 liters		

Connection

Cable area of internal connection cables	70 mm ²	End-lug (and external cable)	50 mm ²
--	--------------------	------------------------------	--------------------



LBE1400P - Cell data sheet

Charging

Float voltage	1,42 V/Cell	High rate voltage (min)	1,47 V/Cell
Single-level voltage	1,43 V/Cell		

Resistance/Short circuit

Internal resistance	0,12 mOhm	Short circuit current	11646 A
---------------------	-----------	-----------------------	---------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	144	178	280	448	598	720	922	1.189	1.333	1.432	1.539	1.765	1.960	2.100	2.520	2.708
1,05	143	178	277	434	542	618	771	1.006	1.112	1.153	1.281	1.462	1.577	1.723	2.069	2.246
1,1	140	172	264	365	459	528	624	783	846	928	1.021	1.073	1.284	1.400	1.704	1.869
1,14	137	161	232	317	380	421	485	620	664	689	775	901	1.047	1.144	1.424	1.577
1,16	129	147	201	272	324	351	398	521	580	627	687	822	955	1.044	1.299	1.438

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	167	204	313	479	625	744	943	1.201	1.342	1.438	1.542	1.765	1.960	2.100	2.520	2.708
1,05	166	205	315	478	587	664	822	1.063	1.172	1.214	1.347	1.535	1.655	1.809	2.173	2.358
1,1	164	200	304	413	514	590	692	865	933	1.022	1.125	1.180	1.413	1.540	1.875	2.056
1,14	161	189	271	366	437	483	555	708	758	786	884	1.027	1.194	1.305	1.624	1.797
1,16	151	173	236	318	378	408	463	605	673	727	797	953	1.108	1.211	1.507	1.668



LBE1400P - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,7	7,85	5,00	3,12	2,34	1,95	1,52	1,18	1,05	0,98	0,91	0,79	0,71	0,67	0,56	0,52
1,05	9,8	7,88	5,05	3,23	2,58	2,26	1,81	1,39	1,26	1,21	1,09	0,96	0,89	0,81	0,68	0,62
1,1	10,0	8,16	5,31	3,83	3,05	2,65	2,25	1,79	1,66	1,51	1,37	1,31	1,09	1,00	0,82	0,75
1,14	10,2	8,68	6,04	4,42	3,69	3,33	2,89	2,26	2,11	2,03	1,81	1,55	1,34	1,22	0,98	0,89
1,16	10,9	9,5	6,98	5,15	4,32	3,99	3,52	2,69	2,41	2,23	2,04	1,70	1,47	1,34	1,08	0,97

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,38	6,87	4,47	2,92	2,24	1,88	1,49	1,17	1,04	0,97	0,91	0,79	0,71	0,67	0,56	0,52
1,05	8,41	6,83	4,45	2,93	2,38	2,11	1,70	1,32	1,19	1,15	1,04	0,91	0,85	0,77	0,64	0,59
1,1	8,55	7,01	4,60	3,39	2,72	2,37	2,02	1,62	1,50	1,37	1,24	1,19	0,99	0,91	0,75	0,68
1,14	8,71	7,41	5,17	3,82	3,20	2,90	2,52	1,98	1,85	1,78	1,58	1,36	1,17	1,07	0,86	0,78
1,16	9,27	8,09	5,94	4,41	3,71	3,43	3,03	2,31	2,08	1,93	1,76	1,47	1,26	1,16	0,93	0,84