




LBE1500P - Cell data sheet

Classification

Brand	Alcad
Cell type	LBE1500P
Cell P/N	310548581
Capacity at 5 hours rate	1.500 Ah
IEC Designation	KL1500P
According to IEC 60623	



Wiring principle



Crosswise

Physical data

Overall height	410 mm	Weight per cell	64,2 Kg
Cell height	400 mm		
Width	195 mm		
Length	487 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	6
Separator type	Grid	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	
Terminal size	M10 SW 16 mm		
		Handle	Yes

Plates

Positive		Negative	
Type of plates	Pocket	Type of plates	Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	16,6 liters		

Connection

Cable area of internal connection cables	70 mm ²	End-lug (and external cable)	50 mm ²
--	--------------------	------------------------------	--------------------



LBE1500P - Cell data sheet

Charging

Float voltage	1,42 V/Cell	High rate voltage (min)	1,47 V/Cell
Single-level voltage	1,43 V/Cell		

Resistance/Short circuit

Internal resistance	0,11 mOhm	Short circuit current	12478 A
---------------------	-----------	-----------------------	---------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	155	191	300	480	641	771	988	1.274	1.429	1.534	1.649	1.891	2.100	2.250	2.700	2.902
1,05	153	190	297	465	580	662	827	1.078	1.191	1.235	1.372	1.566	1.689	1.846	2.217	2.407
1,1	150	184	282	391	491	566	668	839	906	994	1.094	1.149	1.376	1.500	1.826	2.002
1,14	147	173	248	339	407	451	519	664	711	738	830	965	1.122	1.226	1.526	1.689
1,16	138	158	215	291	347	376	426	558	621	671	736	880	1.023	1.118	1.392	1.541

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	179	218	335	514	670	797	1.010	1.287	1.437	1.541	1.653	1.891	2.100	2.250	2.700	2.902
1,05	178	220	337	512	629	712	881	1.139	1.256	1.301	1.443	1.645	1.774	1.938	2.328	2.527
1,1	175	214	326	443	551	632	742	927	999	1.095	1.205	1.264	1.514	1.650	2.009	2.203
1,14	172	202	290	392	468	517	595	759	812	842	947	1.100	1.279	1.398	1.740	1.926
1,16	162	185	253	340	405	437	496	648	721	779	854	1.021	1.187	1.297	1.615	1.787



LBE1500P - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,7	7,85	5,00	3,12	2,34	1,95	1,52	1,18	1,05	0,98	0,91	0,79	0,71	0,67	0,56	0,52
1,05	9,8	7,88	5,05	3,23	2,58	2,26	1,81	1,39	1,26	1,21	1,09	0,96	0,89	0,81	0,68	0,62
1,1	10,0	8,16	5,31	3,83	3,05	2,65	2,25	1,79	1,66	1,51	1,37	1,31	1,09	1,00	0,82	0,75
1,14	10,2	8,68	6,04	4,42	3,69	3,33	2,89	2,26	2,11	2,03	1,81	1,55	1,34	1,22	0,98	0,89
1,16	10,9	9,5	6,98	5,15	4,32	3,99	3,52	2,69	2,41	2,23	2,04	1,70	1,47	1,34	1,08	0,97

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,38	6,87	4,47	2,92	2,24	1,88	1,49	1,17	1,04	0,97	0,91	0,79	0,71	0,67	0,56	0,52
1,05	8,41	6,83	4,45	2,93	2,38	2,11	1,70	1,32	1,19	1,15	1,04	0,91	0,85	0,77	0,64	0,59
1,1	8,55	7,01	4,60	3,39	2,72	2,37	2,02	1,62	1,50	1,37	1,24	1,19	0,99	0,91	0,75	0,68
1,14	8,71	7,41	5,17	3,82	3,20	2,90	2,52	1,98	1,85	1,78	1,58	1,36	1,17	1,07	0,86	0,78
1,16	9,27	8,09	5,94	4,41	3,71	3,43	3,03	2,31	2,08	1,93	1,76	1,47	1,26	1,16	0,93	0,84