




LBE400P - Cell data sheet

Classification

Brand	Alcad
Cell type	LBE400P
Cell P/N	311031881
Capacity at 5 hours rate	400 Ah
IEC Designation	KL400P
According to	IEC 60623



Wiring principle



Crosswise

Physical data

Overall height	410 mm		
Cell height	400 mm		
Width	195 mm	Weight per cell	18,0 Kg
Length	146 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	2
Separator type	Grid	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	
Terminal size	M10 SW 16 mm	Handle	Yes

Plates

Positive		Negative	
Type of plates	Pocket	Type of plates	Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	4,7 liters		

Connection

Cable area of internal connection cables	70 mm ²	End-lug (and external cable)	35 mm ²
--	--------------------	------------------------------	--------------------

ALCAD confidential and proprietary. The data herein given are for information purposes only and are not binding on ALCAD. They may be modified without prior notice. Please contact an ALCAD representative in order to obtain confirmation of the above data.

Visit our website at www.alcad.com

380603 00000000-0000-0000-0000-000000000000 Version: 3.5, Last updated on 01/2024, Referential data
5/13/2024



LBE400P - Cell data sheet

Charging

Float voltage	1,42 V/Cell	High rate voltage (min)	1,47 V/Cell
Single-level voltage	1,43 V/Cell		

Resistance/Short circuit

Internal resistance	0,41 mOhm	Short circuit current	3328 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	41,2	51,0	80,0	128	171	206	263	340	381	409	440	504	560	600	720	774
1,05	40,9	50,8	79,1	124	155	177	220	287	318	329	366	418	450	492	591	642
1,1	40,0	49,0	75,3	104	131	151	178	224	242	265	292	306	367	400	487	534
1,14	39,1	46,1	66,3	90,4	108	120	139	177	190	197	221	257	299	327	407	450
1,16	36,7	42,1	57,3	77,6	92,6	100	114	149	166	179	196	235	273	298	371	411

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	47,8	58,2	89,4	137	179	213	269	343	383	411	441	504	560	600	720	774
1,05	47,6	58,5	89,9	137	168	190	235	304	335	347	385	439	473	517	621	674
1,1	46,8	57,0	86,9	118	147	168	198	247	267	292	321	337	404	440	536	587
1,14	45,9	54,0	77,4	105	125	138	159	202	216	224	252	293	341	373	464	514
1,16	43,2	49,4	67,4	90,8	108	117	132	173	192	208	228	272	317	346	431	477

ALCAD confidential and proprietary. The data herein given are for information purposes only and are not binding on ALCAD. They may be modified without prior notice. Please contact an ALCAD representative in order to obtain confirmation of the above data.

Visit our website at www.alcad.com

380603 00000000-0000-0000-0000-000000000000 Version: 3.5, Last updated on 01/2024, Referential data 5/13/2024



LBE400P - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,7	7,85	5,00	3,12	2,34	1,95	1,52	1,18	1,05	0,98	0,91	0,79	0,71	0,67	0,56	0,52
1,05	9,8	7,88	5,05	3,23	2,58	2,26	1,81	1,39	1,26	1,21	1,09	0,96	0,89	0,81	0,68	0,62
1,1	10,0	8,16	5,31	3,83	3,05	2,65	2,25	1,79	1,66	1,51	1,37	1,31	1,09	1,00	0,82	0,75
1,14	10,2	8,68	6,04	4,42	3,69	3,33	2,89	2,26	2,11	2,03	1,81	1,55	1,34	1,22	0,98	0,89
1,16	10,9	9,5	6,98	5,15	4,32	3,99	3,52	2,69	2,41	2,23	2,04	1,70	1,47	1,34	1,08	0,97

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,38	6,87	4,47	2,92	2,24	1,88	1,49	1,17	1,04	0,97	0,91	0,79	0,71	0,67	0,56	0,52
1,05	8,41	6,83	4,45	2,93	2,38	2,11	1,70	1,32	1,19	1,15	1,04	0,91	0,85	0,77	0,64	0,59
1,1	8,55	7,01	4,60	3,39	2,72	2,37	2,02	1,62	1,50	1,37	1,24	1,19	0,99	0,91	0,75	0,68
1,14	8,71	7,41	5,17	3,82	3,20	2,90	2,52	1,98	1,85	1,78	1,58	1,36	1,17	1,07	0,86	0,78
1,16	9,27	8,09	5,94	4,41	3,71	3,43	3,03	2,31	2,08	1,93	1,76	1,47	1,26	1,16	0,93	0,84

ALCAD confidential and proprietary. The data herein given are for information purposes only and are not binding on ALCAD. They may be modified without prior notice. Please contact an ALCAD representative in order to obtain confirmation of the above data.

Visit our website at www.alcad.com

380603 00000000-0000-0000-0000-000000000000 Version: 3.5, Last updated on 01/2024, Referential data
5/13/2024