




LBE980P - Cell data sheet

Classification

Brand	Alcad
Cell type	LBE980P
Cell P/N	311032481
Capacity at 5 hours rate	980 Ah
IEC Designation	KL980P
According to IEC 60623	



Wiring principle



Crosswise

Physical data

Overall height	410 mm		
Cell height	400 mm		
Width	195 mm	Weight per cell	41,0 Kg
Length	317 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	4
Separator type	Grid	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	
Terminal size	M10 SW 16 mm		
		Handle	Yes

Plates

Positive		Negative	
Type of plates	Pocket	Type of plates	Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	10,7 liters		

Connection

Cable area of internal connection cables	70 mm ²	End-lug (and external cable)	50 mm ²
--	--------------------	------------------------------	--------------------



LBE980P - Cell data sheet

Charging

Float voltage	1,42 V/Cell	High rate voltage (min)	1,47 V/Cell
Single-level voltage	1,43 V/Cell		

Resistance/Short circuit

Internal resistance	0,17 mOhm	Short circuit current	8152 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	101	125	196	314	418	504	646	832	933	1.002	1.077	1.236	1.372	1.470	1.764	1.896
1,05	100	124	194	304	379	433	540	704	778	807	896	1.023	1.104	1.206	1.449	1.572
1,1	98,0	120	184	256	321	370	436	548	592	649	715	751	899	980	1.193	1.308
1,14	95,9	113	162	222	266	294	339	434	465	482	542	631	733	801	997	1.104
1,16	90,0	103	140	190	227	245	278	365	406	439	481	575	668	731	909	1.007

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	117	143	219	336	438	521	660	841	939	1.006	1.080	1.236	1.372	1.470	1.764	1.896
1,05	117	143	220	334	411	465	576	744	820	850	943	1.075	1.159	1.266	1.521	1.651
1,1	115	140	213	289	360	413	485	606	653	716	787	826	989	1.078	1.312	1.439
1,14	112	132	190	256	306	338	389	496	530	550	619	719	836	913	1.137	1.258
1,16	106	121	165	222	264	286	324	424	471	509	558	667	775	848	1.055	1.168



LBE980P - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,7	7,85	5,00	3,12	2,34	1,95	1,52	1,18	1,05	0,98	0,91	0,79	0,71	0,67	0,56	0,52
1,05	9,8	7,88	5,05	3,23	2,58	2,26	1,81	1,39	1,26	1,21	1,09	0,96	0,89	0,81	0,68	0,62
1,1	10,0	8,16	5,31	3,83	3,05	2,65	2,25	1,79	1,66	1,51	1,37	1,31	1,09	1,00	0,82	0,75
1,14	10,2	8,68	6,04	4,42	3,69	3,33	2,89	2,26	2,11	2,03	1,81	1,55	1,34	1,22	0,98	0,89
1,16	10,9	9,5	6,98	5,15	4,32	3,99	3,52	2,69	2,41	2,23	2,04	1,70	1,47	1,34	1,08	0,97

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,38	6,87	4,47	2,92	2,24	1,88	1,49	1,17	1,04	0,97	0,91	0,79	0,71	0,67	0,56	0,52
1,05	8,41	6,83	4,45	2,93	2,38	2,11	1,70	1,32	1,19	1,15	1,04	0,91	0,85	0,77	0,64	0,59
1,1	8,55	7,01	4,60	3,39	2,72	2,37	2,02	1,62	1,50	1,37	1,24	1,19	0,99	0,91	0,75	0,68
1,14	8,71	7,41	5,17	3,82	3,20	2,90	2,52	1,98	1,85	1,78	1,58	1,36	1,17	1,07	0,86	0,78
1,16	9,27	8,09	5,94	4,41	3,71	3,43	3,03	2,31	2,08	1,93	1,76	1,47	1,26	1,16	0,93	0,84