




LCE100P - Cell data sheet

Classification

Brand	Alcad
Cell type	LCE100P
Cell P/N	311033751
Capacity at 5 hours rate	100 Ah
IEC Designation	KL100P
According to IEC 60623	



Wiring principle



Normal

Physical data

Overall height	357 mm		
Cell height	349 mm		
Width	192 mm	Weight per cell	6,8 Kg
Length	68 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	1
Separator type	Grid	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	
Terminal size	M10 SW 16 mm		
		Handle	No

Plates

Positive		Negative	
Type of plates	Pocket	Type of plates	Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	2,4 liters		

Connection

Cable area of internal connection cables	16 mm ²	End-lug (and external cable)	16 mm ²
--	--------------------	------------------------------	--------------------



LCE100P - Cell data sheet

Charging

Float voltage	1,42 V/Cell	High rate voltage (min)	1,47 V/Cell
Single-level voltage	1,43 V/Cell		

Resistance/Short circuit

Internal resistance	1,60 mOhm	Short circuit current	980 A
---------------------	-----------	-----------------------	-------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	10,1	12,6	20,0	32,0	43,4	52,8	67,9	86,8	97,9	104	110	132	151	161	205	228
1,05	10,0	12,5	19,6	31,3	38,4	45,1	55,9	73,4	83,5	89,2	96,7	104	121	133	169	187
1,1	9,9	12,1	18,7	26,7	33,7	39,5	46,3	59,2	65,3	66,3	73,0	86,1	97,9	109	137	153
1,14	9,6	11,3	16,4	22,9	28,4	31,6	36,3	45,8	52,2	52,3	59,8	64,4	80,0	88,5	113	128
1,16	9,01	10,3	14,2	19,7	24,2	26,4	29,8	38,5	45,6	47,6	53,0	58,8	73,0	80,8	103	117

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	11,7	14,4	22,4	34,2	45,4	54,6	69,4	87,7	98,5	104	110	132	151	161	205	228
1,05	11,6	14,4	22,3	34,5	41,6	48,5	59,6	77,6	88,0	93,9	102	109	127	140	178	196
1,1	11,6	14,1	21,5	30,2	37,8	44,1	51,4	65,4	72,0	73,0	80,3	94,7	108	120	151	169
1,14	11,3	13,2	19,2	26,5	32,6	36,3	41,6	52,3	59,5	59,7	68,2	73,4	91,2	101	129	146
1,16	10,6	12,1	16,7	23,0	28,2	30,7	34,6	44,7	52,9	55,3	61,5	68,2	84,6	93,7	120	135



LCE100P - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,9	7,92	5,00	3,12	2,30	1,90	1,47	1,15	1,02	0,96	0,91	0,76	0,66	0,62	0,49	0,44
1,05	10,0	8,00	5,10	3,19	2,60	2,22	1,79	1,36	1,20	1,12	1,03	0,96	0,83	0,75	0,59	0,54
1,1	10,1	8,24	5,36	3,75	2,97	2,53	2,16	1,69	1,53	1,51	1,37	1,16	1,02	0,91	0,73	0,65
1,14	10,4	8,87	6,10	4,36	3,53	3,16	2,76	2,18	1,92	1,91	1,67	1,55	1,25	1,13	0,88	0,78
1,16	11,1	9,7	7,03	5,07	4,13	3,79	3,36	2,60	2,19	2,10	1,89	1,70	1,37	1,24	0,97	0,86

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,54	6,93	4,47	2,92	2,20	1,83	1,44	1,14	1,02	0,96	0,91	0,76	0,66	0,62	0,49	0,44
1,05	8,59	6,94	4,49	2,90	2,40	2,06	1,68	1,29	1,14	1,07	0,98	0,91	0,79	0,71	0,56	0,51
1,1	8,63	7,09	4,64	3,31	2,65	2,27	1,95	1,53	1,39	1,37	1,24	1,06	0,93	0,83	0,66	0,59
1,14	8,88	7,57	5,22	3,77	3,06	2,75	2,41	1,91	1,68	1,67	1,47	1,36	1,10	0,99	0,77	0,69
1,16	9,45	8,27	5,98	4,34	3,54	3,26	2,89	2,24	1,89	1,81	1,63	1,47	1,18	1,07	0,83	0,74