




LCE185P - Cell data sheet

Classification

Brand	Alcad
Cell type	LCE185P
Cell P/N	310549951
Capacity at 5 hours rate	185 Ah
IEC Designation	KL185P
According to IEC 60623	



Wiring principle Normal



Physical data

Overall height	357 mm		
Cell height	349 mm		
Width	192 mm	Weight per cell	9,8 Kg
Length	93 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	1
Separator type	Grid	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	
Terminal size	M10 SW 16 mm		
		Handle	No

Plates

Positive		Negative	
Type of plates	Pocket	Type of plates	Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	3,2 liters		

Connection

Cable area of internal connection cables	35 mm ²	End-lug (and external cable)	35 mm ²
--	--------------------	------------------------------	--------------------



LCE185P - Cell data sheet

Charging

Float voltage	1,42 V/Cell	High rate voltage (min)	1,47 V/Cell
Single-level voltage	1,43 V/Cell		

Resistance/Short circuit

Internal resistance	0,86 mOhm	Short circuit current	1814 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	18,7	23,4	37,0	59,2	80,4	97,6	126	161	181	192	203	244	279	298	380	422
1,05	18,5	23,1	36,3	58,0	71,0	83,5	103	136	154	165	179	193	224	247	313	345
1,1	18,3	22,4	34,5	49,3	62,3	73,2	85,6	110	121	123	135	159	181	203	254	284
1,14	17,8	20,9	30,3	42,4	52,4	58,5	67,1	84,7	96,5	96,8	111	119	148	164	210	237
1,16	16,7	19,0	26,3	36,5	44,8	48,8	55,1	71,2	84,3	88,1	98,0	109	135	149	191	216

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	21,7	26,7	41,4	63,4	84,1	101	128	162	182	193	204	244	279	298	380	422
1,05	21,5	26,7	41,2	63,8	77,0	89,8	110	144	163	174	188	203	235	259	329	363
1,1	21,4	26,1	39,8	55,8	69,8	81,6	95,0	121	133	135	149	175	199	223	279	312
1,14	20,8	24,4	35,4	49,1	60,4	67,2	76,9	96,8	110	110	126	136	169	187	239	270
1,16	19,6	22,4	30,9	42,6	52,2	56,8	64,0	82,7	97,8	102	114	126	157	173	222	251



LCE185P - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,9	7,92	5,00	3,12	2,30	1,90	1,47	1,15	1,02	0,96	0,91	0,76	0,66	0,62	0,49	0,44
1,05	10,0	8,00	5,10	3,19	2,60	2,22	1,79	1,36	1,20	1,12	1,03	0,96	0,83	0,75	0,59	0,54
1,1	10,1	8,24	5,36	3,75	2,97	2,53	2,16	1,69	1,53	1,51	1,37	1,16	1,02	0,91	0,73	0,65
1,14	10,4	8,87	6,10	4,36	3,53	3,16	2,76	2,18	1,92	1,91	1,67	1,55	1,25	1,13	0,88	0,78
1,16	11,1	9,7	7,03	5,07	4,13	3,79	3,36	2,60	2,19	2,10	1,89	1,70	1,37	1,24	0,97	0,86

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,54	6,93	4,47	2,92	2,20	1,83	1,44	1,14	1,02	0,96	0,91	0,76	0,66	0,62	0,49	0,44
1,05	8,59	6,94	4,49	2,90	2,40	2,06	1,68	1,29	1,14	1,07	0,98	0,91	0,79	0,71	0,56	0,51
1,1	8,63	7,09	4,64	3,31	2,65	2,27	1,95	1,53	1,39	1,37	1,24	1,06	0,93	0,83	0,66	0,59
1,14	8,88	7,57	5,22	3,77	3,06	2,75	2,41	1,91	1,68	1,67	1,47	1,36	1,10	0,99	0,77	0,69
1,16	9,45	8,27	5,98	4,34	3,54	3,26	2,89	2,24	1,89	1,81	1,63	1,47	1,18	1,07	0,83	0,74