




LCE75P - Cell data sheet

Classification

Brand	Alcad
Cell type	LCE75P
Cell P/N	310549551
Capacity at 5 hours rate	75 Ah
IEC Designation	KL75P
According to IEC 60623	



Wiring principle Normal



Physical data

Overall height	357 mm	Weight per cell	6,1 Kg
Cell height	349 mm		
Width	192 mm		
Length	68 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	1
Separator type	Grid	Terminal material	Steel
Connection torque	20,0 +/- 2,0 Nm	Vent type	
Terminal size	M8 SW 13 mm	Handle	No

Plates

Positive		Negative	
Type of plates	Pocket	Type of plates	Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	2,7 liters		

Connection

Cable area of internal connection cables	16 mm ²	End-lug (and external cable)	16 mm ²
--	--------------------	------------------------------	--------------------



LCE75P - Cell data sheet

Charging

Float voltage	1,42 V/Cell	High rate voltage (min)	1,47 V/Cell
Single-level voltage	1,43 V/Cell		

Resistance/Short circuit

Internal resistance	2,13 mOhm	Short circuit current	735 A
---------------------	-----------	-----------------------	-------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	7,58	9,47	15,0	24,0	32,6	39,6	50,9	65,1	73,4	78,0	82,4	99,0	113	121	154	171
1,05	7,50	9,38	14,7	23,5	28,8	33,8	42,0	55,1	62,6	66,9	72,5	78,2	90,7	100	127	140
1,1	7,43	9,10	14,0	20,0	25,3	29,6	34,7	44,4	49,0	49,7	54,7	64,6	73,4	82,1	103	115
1,14	7,20	8,46	12,3	17,2	21,3	23,7	27,2	34,3	39,1	39,2	44,9	48,3	60,0	66,4	85,1	96,0
1,16	6,76	7,72	10,7	14,8	18,2	19,8	22,3	28,9	34,2	35,7	39,8	44,1	54,7	60,6	77,6	87,6

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,78	10,8	16,8	25,7	34,1	40,9	52,0	65,7	73,9	78,3	82,5	99,0	113	121	154	171
1,05	8,73	10,8	16,7	25,9	31,2	36,4	44,7	58,2	66,0	70,4	76,3	82,1	95,2	105	133	147
1,1	8,69	10,6	16,2	22,6	28,3	33,1	38,5	49,1	54,0	54,8	60,2	71,0	80,7	90,3	113	126
1,14	8,45	9,9	14,4	19,9	24,5	27,2	31,2	39,2	44,6	44,8	51,2	55,1	68,4	75,7	97,0	109
1,16	7,94	9,07	12,5	17,3	21,2	23,0	26,0	33,5	39,7	41,4	46,1	51,1	63,5	70,3	90,0	102



LCE75P - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,9	7,92	5,00	3,12	2,30	1,90	1,47	1,15	1,02	0,96	0,91	0,76	0,66	0,62	0,49	0,44
1,05	10,0	8,00	5,10	3,19	2,60	2,22	1,79	1,36	1,20	1,12	1,03	0,96	0,83	0,75	0,59	0,54
1,1	10,1	8,24	5,36	3,75	2,97	2,53	2,16	1,69	1,53	1,51	1,37	1,16	1,02	0,91	0,73	0,65
1,14	10,4	8,87	6,10	4,36	3,53	3,16	2,76	2,18	1,92	1,91	1,67	1,55	1,25	1,13	0,88	0,78
1,16	11,1	9,7	7,03	5,07	4,13	3,79	3,36	2,60	2,19	2,10	1,89	1,70	1,37	1,24	0,97	0,86

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,54	6,93	4,47	2,92	2,20	1,83	1,44	1,14	1,02	0,96	0,91	0,76	0,66	0,62	0,49	0,44
1,05	8,59	6,94	4,49	2,90	2,40	2,06	1,68	1,29	1,14	1,07	0,98	0,91	0,79	0,71	0,56	0,51
1,1	8,63	7,09	4,64	3,31	2,65	2,27	1,95	1,53	1,39	1,37	1,24	1,06	0,93	0,83	0,66	0,59
1,14	8,88	7,57	5,22	3,77	3,06	2,75	2,41	1,91	1,68	1,67	1,47	1,36	1,10	0,99	0,77	0,69
1,16	9,45	8,27	5,98	4,34	3,54	3,26	2,89	2,24	1,89	1,81	1,63	1,47	1,18	1,07	0,83	0,74