




MB370P - Cell data sheet

Classification

Brand	Alcad
Cell type	MB370P
Cell P/N	310048981
Capacity at 5 hours rate	370 Ah
IEC Designation	KM370P
According to IEC 60623	



Wiring principle



Crosswise

Physical data

Overall height	410 mm		
Cell height	400 mm		
Width	195 mm	Weight per cell	20,4 Kg
Length	159 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	2
Separator type	Grid	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	
Terminal size	M10 SW 16 mm		
		Handle	Yes

Plates

Positive		Negative	
Type of plates	Pocket	Type of plates	Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	5,3 liters		

Connection

Cable area of internal connection cables	95 mm ²	End-lug (and external cable)	95 mm ²
--	--------------------	------------------------------	--------------------



MB370P - Cell data sheet

Charging

Float voltage	1,4 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,43 V/Cell		

Resistance/Short circuit

Internal resistance	0,23 mOhm	Short circuit current	5813 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	37,7	46,6	74,0	121	177	220	310	422	489	529	603	710	959	1.070	1.278	1.352
1,05	37,3	46,2	73,3	120	166	212	280	358	422	459	502	582	814	915	1.079	1.162
1,1	36,7	45,6	72,0	112	155	187	228	285	346	360	411	493	687	766	904	960
1,14	35,7	44,3	69,7	105	135	156	183	223	256	277	318	396	554	614	710	732
1,16	34,7	42,6	64,2	97,3	114	123	153	191	219	228	255	317	465	518	582	619

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	44,9	55,0	86,4	135	188	231	320	428	493	532	605	710	959	1.070	1.278	1.352
1,05	44,5	54,8	85,9	134	182	230	300	379	445	484	528	611	855	961	1.133	1.220
1,1	43,8	54,1	84,7	128	175	210	254	315	382	397	453	542	756	843	995	1.057
1,14	42,6	52,6	82,2	122	156	180	210	255	292	316	362	452	632	700	809	834
1,16	41,5	50,6	75,8	114	133	144	178	222	254	265	296	367	539	600	676	718



MB370P - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,8	7,94	5,00	3,06	2,09	1,68	1,19	0,88	0,76	0,70	0,61	0,52	0,39	0,35	0,29	0,27
1,05	9,9	8,00	5,05	3,09	2,23	1,74	1,32	1,03	0,88	0,81	0,74	0,64	0,45	0,40	0,34	0,32
1,1	10,1	8,12	5,14	3,31	2,39	1,98	1,62	1,30	1,07	1,03	0,90	0,75	0,54	0,48	0,41	0,39
1,14	10,4	8,36	5,31	3,52	2,73	2,37	2,02	1,66	1,45	1,34	1,16	0,93	0,67	0,60	0,52	0,51
1,16	10,7	8,70	5,77	3,80	3,25	3,00	2,42	1,94	1,69	1,62	1,45	1,17	0,80	0,71	0,64	0,60

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,24	6,72	4,28	2,74	1,96	1,60	1,16	0,86	0,75	0,70	0,61	0,52	0,39	0,35	0,29	0,27
1,05	8,31	6,75	4,31	2,76	2,03	1,61	1,23	0,98	0,83	0,76	0,70	0,61	0,43	0,38	0,33	0,30
1,1	8,45	6,84	4,37	2,89	2,11	1,76	1,46	1,17	0,97	0,93	0,82	0,68	0,49	0,44	0,37	0,35
1,14	8,68	7,03	4,50	3,03	2,36	2,06	1,76	1,45	1,27	1,17	1,02	0,82	0,59	0,53	0,46	0,44
1,16	8,92	7,31	4,88	3,24	2,78	2,57	2,08	1,67	1,46	1,40	1,25	1,01	0,69	0,62	0,55	0,52