



MC100P - Cell data sheet

Classification

Brand	Alcad
Cell type	MC100P
Cell P/N	311038051
Capacity at 5 hours rate	100 Ah
IEC Designation	KM100P
According to IEC 60623	



Wiring principle

Normal



Physical data

Overall height	357 mm		
Cell height	349 mm		
Width	192 mm	Weight per cell	7,4 Kg
Length	68 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	1
Separator type	Grid	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	
Terminal size	M10 SW 16 mm		
		Handle	No

Plates

Positive		Negative	
Type of plates	Pocket	Type of plates	Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	2,3 liters		

Connection

Cable area of internal connection cables	70 mm ²	End-lug (and external cable)	50 mm ²
--	--------------------	------------------------------	--------------------



MC100P - Cell data sheet

Charging

Float voltage	1,4 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,43 V/Cell		

Resistance/Short circuit

Internal resistance	0,78 mOhm	Short circuit current	1702 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	10,2	12,6	20,0	32,8	47,8	59,4	83,9	115	133	145	165	197	270	306	371	396
1,05	10,1	12,5	19,8	32,3	44,9	57,3	75,6	97,4	115	125	139	163	232	262	316	338
1,1	9,9	12,3	19,5	30,1	41,9	50,6	61,6	77,6	95,0	100	114	138	195	220	262	302
1,14	9,7	12,0	18,8	28,3	36,0	41,0	47,3	58,2	66,1	72,0	82,9	104	147	165	192	198
1,16	9,40	11,5	17,3	26,2	30,3	32,4	39,3	49,7	56,5	59,4	66,6	83,0	123	139	157	168

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	12,1	14,9	23,3	36,6	51,0	62,3	86,5	116	134	146	166	197	270	306	371	396
1,05	12,0	14,8	23,2	36,2	49,2	62,2	81,1	103	121	132	147	171	243	275	332	355
1,1	11,8	14,6	23,0	34,5	47,3	56,8	68,7	85,9	105	110	125	152	215	242	288	332
1,14	11,6	14,3	22,2	32,9	41,6	47,2	54,2	66,5	75,5	82,2	94,6	119	167	188	219	226
1,16	11,2	13,7	20,4	30,7	35,4	37,8	45,8	57,7	65,6	69,0	77,2	96,3	143	161	182	195



MC100P - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,8	7,94	5,00	3,05	2,09	1,68	1,19	0,87	0,75	0,69	0,60	0,51	0,37	0,33	0,27	0,25
1,05	9,9	8,00	5,04	3,10	2,23	1,74	1,32	1,03	0,87	0,80	0,72	0,61	0,43	0,38	0,32	0,30
1,1	10,1	8,12	5,12	3,32	2,39	1,97	1,62	1,29	1,05	1,00	0,88	0,72	0,51	0,45	0,38	0,33
1,14	10,3	8,33	5,32	3,53	2,77	2,44	2,12	1,72	1,51	1,39	1,21	0,96	0,68	0,61	0,52	0,50
1,16	10,6	8,67	5,78	3,82	3,30	3,08	2,54	2,01	1,77	1,68	1,50	1,20	0,81	0,72	0,64	0,60

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,26	6,72	4,28	2,73	1,96	1,61	1,16	0,86	0,74	0,69	0,60	0,51	0,37	0,33	0,27	0,25
1,05	8,32	6,75	4,30	2,77	2,03	1,61	1,23	0,97	0,82	0,76	0,68	0,58	0,41	0,36	0,30	0,28
1,1	8,45	6,85	4,35	2,90	2,11	1,76	1,46	1,16	0,95	0,91	0,80	0,66	0,47	0,41	0,35	0,30
1,14	8,66	7,01	4,51	3,04	2,40	2,12	1,84	1,50	1,32	1,22	1,06	0,84	0,60	0,53	0,46	0,44
1,16	8,90	7,29	4,89	3,25	2,82	2,64	2,19	1,73	1,52	1,45	1,29	1,04	0,70	0,62	0,55	0,51