




VTX 1 L 1220 - Cell data sheet

Classification

Brand	Alcad
Cell type	VTX 1 L 1220
Cell P/N	310559781
Capacity at 5 hours rate	1.220 Ah
IEC Designation	KGL1220P
According to IEC 62259	



Wiring principle



Crosswise

Physical data

Overall height	411 mm		
Cell height			
Width	195 mm	Weight per cell	51,3 Kg
Length	387 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	5
Separator type	Felt	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	Low pressure flame arresting vent (large)
Terminal size	M10 SW 16 mm	Handle	Yes

Plates

Positive		Negative	
Type of plates	Maintenance Free Pocket	Type of plates	Maintenance Free Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	12,7 liters		

Connection

Cable area of internal connection cables	70 mm ²	End-lug (and external cable)	50 mm ²
--	--------------------	------------------------------	--------------------



VTX 1 L 1220 - Cell data sheet

Charging

Float voltage	1,42 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,42 V/Cell		

Resistance/Short circuit

Internal resistance	0,20 mOhm	Short circuit current	6834 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	127	157	244	393	511	586	688	837	911	966	1.018	1.122	1.122	1.229	1.450	1.589
1,05	125	155	241	356	445	504	575	685	746	769	812	891	942	1.022	1.214	1.326
1,1	122	150	224	308	372	409	461	549	592	619	651	701	772	843	1.001	1.080
1,14	116	138	190	240	287	317	355	415	450	482	518	586	608	675	801	853

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	147	180	273	420	535	606	703	845	917	970	1.020	1.122	1.122	1.229	1.450	1.589
1,05	146	178	274	392	482	542	613	724	787	810	853	935	989	1.073	1.274	1.392
1,1	143	175	258	348	417	456	511	606	653	682	717	771	850	928	1.101	1.188
1,14	136	162	222	278	330	364	407	474	514	549	591	668	693	769	913	972



VTX 1 L 1220 - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,6	7,76	5,00	3,11	2,39	2,08	1,77	1,46	1,34	1,26	1,20	1,09	1,09	0,99	0,84	0,77
1,05	9,7	7,89	5,06	3,43	2,74	2,42	2,12	1,78	1,64	1,59	1,50	1,37	1,29	1,19	1,01	0,92
1,1	10,0	8,12	5,45	3,97	3,28	2,98	2,65	2,22	2,06	1,97	1,87	1,74	1,58	1,45	1,22	1,13
1,14	10,5	8,84	6,41	5,08	4,26	3,85	3,44	2,94	2,71	2,53	2,35	2,08	2,01	1,81	1,52	1,43

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,30	6,79	4,47	2,90	2,28	2,01	1,73	1,44	1,33	1,26	1,20	1,09	1,09	0,99	0,84	0,77
1,05	8,35	6,84	4,45	3,11	2,53	2,25	1,99	1,68	1,55	1,51	1,43	1,30	1,23	1,14	0,96	0,88
1,1	8,55	6,98	4,72	3,50	2,93	2,67	2,39	2,01	1,87	1,79	1,70	1,58	1,44	1,32	1,11	1,03
1,14	8,97	7,55	5,49	4,40	3,70	3,35	3,00	2,57	2,37	2,22	2,06	1,83	1,76	1,59	1,34	1,26