




VTX 1 L 325 - Cell data sheet

Classification

Brand	Alcad		Wiring principle	Normal
Cell type	VTX 1 L 325			
Cell P/N	310558082			
Capacity at 5 hours rate	325 Ah			
IEC Designation	KGL325P			
According to IEC 62259				

Physical data

Overall height	421 mm		
Cell height			
Width	195 mm	Weight per cell	15,1 Kg
Block length - 2 cells	228 mm	Block length - 3 cells	336 mm

Construction

Container material	Polypropylene	No. of terminals/polarity	2
Separator type	Felt	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	Low pressure flame arresting vent (large)
Terminal size	M10 SW 16 mm	Handle	Yes

Plates

Positive		Negative	
Type of plates	Maintenance Free Pocket	Type of plates	Maintenance Free Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	3,5 liters		

Connection

Cable area of internal connection cables	70 mm ²	End-lug (and external cable)	70 mm ²
--	--------------------	------------------------------	--------------------



VTX 1 L 325 - Cell data sheet

Charging

Float voltage	1,42 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,42 V/Cell		

Resistance/Short circuit

Internal resistance	0,74 mOhm	Short circuit current	1821 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	33,8	41,9	65,0	105	136	156	183	223	243	257	271	299	299	327	386	423
1,05	33,4	41,2	64,2	94,8	119	134	153	183	199	205	216	237	251	272	323	353
1,1	32,5	40,0	59,6	82,0	99,1	109	123	146	158	165	173	187	206	225	267	288
1,14	30,9	36,8	50,7	63,9	76,4	84,5	94,6	110	120	128	138	156	162	180	213	227

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	39,1	47,9	72,7	112	142	161	187	225	244	258	272	299	299	327	386	423
1,05	38,9	47,5	73,0	104	129	144	163	193	210	216	227	249	264	286	340	371
1,1	38,0	46,5	68,8	92,8	111	122	136	162	174	182	191	205	226	247	293	316
1,14	36,2	43,1	59,2	73,9	87,9	97,0	108	126	137	146	157	178	185	205	243	259



VTX 1 L 325 - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,6	7,76	5,00	3,11	2,39	2,08	1,77	1,46	1,34	1,26	1,20	1,09	1,09	0,99	0,84	0,77
1,05	9,7	7,89	5,06	3,43	2,74	2,42	2,12	1,78	1,64	1,59	1,50	1,37	1,29	1,19	1,01	0,92
1,1	10,0	8,12	5,45	3,97	3,28	2,98	2,65	2,22	2,06	1,97	1,87	1,74	1,58	1,45	1,22	1,13
1,14	10,5	8,84	6,41	5,08	4,26	3,85	3,44	2,94	2,71	2,53	2,35	2,08	2,01	1,81	1,52	1,43

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,30	6,79	4,47	2,90	2,28	2,01	1,73	1,44	1,33	1,26	1,20	1,09	1,09	0,99	0,84	0,77
1,05	8,35	6,84	4,45	3,11	2,53	2,25	1,99	1,68	1,55	1,51	1,43	1,30	1,23	1,14	0,96	0,88
1,1	8,55	6,98	4,72	3,50	2,93	2,67	2,39	2,01	1,87	1,79	1,70	1,58	1,44	1,32	1,11	1,03
1,14	8,97	7,55	5,49	4,40	3,70	3,35	3,00	2,57	2,37	2,22	2,06	1,83	1,76	1,59	1,34	1,26