




VTX 1 L 515 - Cell data sheet

Classification

Brand	Alcad
Cell type	VTX 1 L 515
Cell P/N	310558481
Capacity at 5 hours rate	515 Ah
IEC Designation	KGL515P
According to IEC 62259	



Wiring principle



Crosswise

Physical data

Overall height	411 mm		
Cell height			
Width	195 mm	Weight per cell	21,4 Kg
Length	171 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	2
Separator type	Felt	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	Low pressure flame arresting vent (large)
Terminal size	M10 SW 16 mm	Handle	Yes

Plates

Positive		Negative	
Type of plates	Maintenance Free Pocket	Type of plates	Maintenance Free Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	5,2 liters		

Connection

Cable area of internal connection cables	70 mm ²	End-lug (and external cable)	50 mm ²
--	--------------------	------------------------------	--------------------



VTX 1 L 515 - Cell data sheet

Charging

Float voltage	1,42 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,42 V/Cell		

Resistance/Short circuit

Internal resistance	0,47 mOhm	Short circuit current	2885 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	53,5	66,4	103	166	216	247	290	353	385	408	430	474	474	519	612	671
1,05	53,0	65,3	102	150	188	213	243	289	315	325	343	376	398	431	512	560
1,1	51,5	63,4	94,4	130	157	173	194	232	250	261	275	296	326	356	423	456
1,14	48,9	58,3	80,3	101	121	134	150	175	190	203	219	247	257	285	338	360

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	62,0	75,9	115	177	226	256	297	357	387	410	430	474	474	519	612	671
1,05	61,6	75,3	116	165	204	229	259	306	332	342	360	395	418	453	538	588
1,1	60,2	73,8	109	147	176	193	216	256	276	288	303	326	359	392	465	501
1,14	57,4	68,2	93,9	117	139	154	172	200	217	232	249	282	293	325	385	410



VTX 1 L 515 - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,6	7,76	5,00	3,11	2,39	2,08	1,77	1,46	1,34	1,26	1,20	1,09	1,09	0,99	0,84	0,77
1,05	9,7	7,89	5,06	3,43	2,74	2,42	2,12	1,78	1,64	1,59	1,50	1,37	1,29	1,19	1,01	0,92
1,1	10,0	8,12	5,45	3,97	3,28	2,98	2,65	2,22	2,06	1,97	1,87	1,74	1,58	1,45	1,22	1,13
1,14	10,5	8,84	6,41	5,08	4,26	3,85	3,44	2,94	2,71	2,53	2,35	2,08	2,01	1,81	1,52	1,43

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,30	6,79	4,47	2,90	2,28	2,01	1,73	1,44	1,33	1,26	1,20	1,09	1,09	0,99	0,84	0,77
1,05	8,35	6,84	4,45	3,11	2,53	2,25	1,99	1,68	1,55	1,51	1,43	1,30	1,23	1,14	0,96	0,88
1,1	8,55	6,98	4,72	3,50	2,93	2,67	2,39	2,01	1,87	1,79	1,70	1,58	1,44	1,32	1,11	1,03
1,14	8,97	7,55	5,49	4,40	3,70	3,35	3,00	2,57	2,37	2,22	2,06	1,83	1,76	1,59	1,34	1,26