




VTX 1 L 560 - Cell data sheet

Classification

Brand	Alcad
Cell type	VTX 1 L 560
Cell P/N	310558581
Capacity at 5 hours rate	560 Ah
IEC Designation	KGL560P
According to IEC 62259	



Physical data

Overall height	411 mm		
Cell height			
Width	195 mm	Weight per cell	23,0 Kg
Length	183 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	2
Separator type	Felt	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	Low pressure flame arresting vent (large)
Terminal size	M10 SW 16 mm	Handle	Yes

Plates

Positive		Negative	
Type of plates	Maintenance Free Pocket	Type of plates	Maintenance Free Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	5,8 liters		

Connection

Cable area of internal connection cables	70 mm ²	End-lug (and external cable)	50 mm ²
--	--------------------	------------------------------	--------------------



VTX 1 L 560 - Cell data sheet

Charging

Float voltage	1,42 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,42 V/Cell		

Resistance/Short circuit

Internal resistance	0,43 mOhm	Short circuit current	3137 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	58,2	72,2	112	180	235	269	316	384	418	444	467	515	515	564	666	730
1,05	57,6	71,0	111	163	204	231	264	314	342	353	373	409	432	469	557	608
1,1	56,0	69,0	103	141	171	188	211	252	272	284	299	322	355	387	459	496
1,14	53,2	63,4	87,4	110	132	146	163	190	207	221	238	269	279	310	368	391

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	67,4	82,5	125	193	245	278	323	388	421	445	468	515	515	564	666	730
1,05	67,0	81,8	126	180	221	249	281	333	361	372	392	429	454	493	585	639
1,1	65,5	80,2	119	160	191	210	235	278	300	313	329	354	390	426	505	545
1,14	62,4	74,2	102	127	151	167	187	218	236	252	271	307	318	353	419	446



VTX 1 L 560 - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,6	7,76	5,00	3,11	2,39	2,08	1,77	1,46	1,34	1,26	1,20	1,09	1,09	0,99	0,84	0,77
1,05	9,7	7,89	5,06	3,43	2,74	2,42	2,12	1,78	1,64	1,59	1,50	1,37	1,29	1,19	1,01	0,92
1,1	10,0	8,12	5,45	3,97	3,28	2,98	2,65	2,22	2,06	1,97	1,87	1,74	1,58	1,45	1,22	1,13
1,14	10,5	8,84	6,41	5,08	4,26	3,85	3,44	2,94	2,71	2,53	2,35	2,08	2,01	1,81	1,52	1,43

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,30	6,79	4,47	2,90	2,28	2,01	1,73	1,44	1,33	1,26	1,20	1,09	1,09	0,99	0,84	0,77
1,05	8,35	6,84	4,45	3,11	2,53	2,25	1,99	1,68	1,55	1,51	1,43	1,30	1,23	1,14	0,96	0,88
1,1	8,55	6,98	4,72	3,50	2,93	2,67	2,39	2,01	1,87	1,79	1,70	1,58	1,44	1,32	1,11	1,03
1,14	8,97	7,55	5,49	4,40	3,70	3,35	3,00	2,57	2,37	2,22	2,06	1,83	1,76	1,59	1,34	1,26