




VTX 1 L 750 - Cell data sheet

Classification

Brand	Alcad
Cell type	VTX 1 L 750
Cell P/N	310558981
Capacity at 5 hours rate	750 Ah
IEC Designation	KGL750P
According to	IEC 62259



Physical data

Overall height	411 mm		
Cell height			
Width	195 mm	Weight per cell	31,4 Kg
Length	243 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	3
Separator type	Felt	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	Low pressure flame arresting vent (large)
Terminal size	M10 SW 16 mm	Handle	Yes

Plates

Positive		Negative	
Type of plates	Maintenance Free Pocket	Type of plates	Maintenance Free Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	7,8 liters		

Connection

Cable area of internal connection cables	70 mm ²	End-lug (and external cable)	50 mm ²
--	--------------------	------------------------------	--------------------



VTX 1 L 750 - Cell data sheet

Charging

Float voltage	1,42 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,42 V/Cell		

Resistance/Short circuit

Internal resistance	0,32 mOhm	Short circuit current	4201 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	78,0	96,7	150	242	314	360	423	515	560	594	626	690	690	755	891	977
1,05	77,1	95,1	148	219	274	310	354	421	459	473	499	547	579	628	746	815
1,1	75,0	92,3	138	189	229	252	283	337	364	381	400	431	475	518	615	664
1,14	71,2	84,8	117	148	176	195	218	255	277	296	319	360	374	415	492	524

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	90,3	110	168	258	329	372	432	520	564	596	627	690	690	755	891	977
1,05	89,8	110	168	241	297	333	377	445	484	498	525	575	608	660	783	856
1,1	87,7	107	159	214	256	281	314	373	402	420	441	474	522	570	677	730
1,14	83,6	99,4	137	171	203	224	250	291	316	338	363	411	426	473	561	598



VTX 1 L 750 - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,6	7,76	5,00	3,11	2,39	2,08	1,77	1,46	1,34	1,26	1,20	1,09	1,09	0,99	0,84	0,77
1,05	9,7	7,89	5,06	3,43	2,74	2,42	2,12	1,78	1,64	1,59	1,50	1,37	1,29	1,19	1,01	0,92
1,1	10,0	8,12	5,45	3,97	3,28	2,98	2,65	2,22	2,06	1,97	1,87	1,74	1,58	1,45	1,22	1,13
1,14	10,5	8,84	6,41	5,08	4,26	3,85	3,44	2,94	2,71	2,53	2,35	2,08	2,01	1,81	1,52	1,43

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,30	6,79	4,47	2,90	2,28	2,01	1,73	1,44	1,33	1,26	1,20	1,09	1,09	0,99	0,84	0,77
1,05	8,35	6,84	4,45	3,11	2,53	2,25	1,99	1,68	1,55	1,51	1,43	1,30	1,23	1,14	0,96	0,88
1,1	8,55	6,98	4,72	3,50	2,93	2,67	2,39	2,01	1,87	1,79	1,70	1,58	1,44	1,32	1,11	1,03
1,14	8,97	7,55	5,49	4,40	3,70	3,35	3,00	2,57	2,37	2,22	2,06	1,83	1,76	1,59	1,34	1,26