




VTX 1 M 1030 - Cell data sheet

Classification

Brand	Alcad
Cell type	VTX 1 M 1030
Cell P/N	310563781
Capacity at 5 hours rate	1.030 Ah
IEC Designation	KGM1030P
According to	IEC 62259



Wiring principle



Crosswise

Physical data

Overall height	411 mm		
Cell height			
Width	195 mm	Weight per cell	56,4 Kg
Length	412 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	5
Separator type	Felt	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	Low pressure flame arresting vent (large)
Terminal size	M10 SW 16 mm	Handle	Yes

Plates

Positive		Negative	
Type of plates	Maintenance Free Pocket	Type of plates	Maintenance Free Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	13,5 liters		

Connection

Cable area of internal connection cables	70 mm²	End-lug (and external cable)	70 mm²
--	--------	------------------------------	--------



VTX 1 M 1030 - Cell data sheet

Charging

Float voltage	1,42 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,42 V/Cell		

Resistance/Short circuit

Internal resistance	0,11 mOhm	Short circuit current	11167 A
---------------------	-----------	-----------------------	---------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	103	128	206	330	484	633	845	1.153	1.302	1.398	1.517	1.759	1.856	2.126	2.421	2.597
1,05	103	127	200	326	476	601	748	959	1.082	1.155	1.245	1.442	1.581	1.801	2.048	2.192
1,1	102	126	197	318	442	518	612	753	826	875	960	1.130	1.305	1.502	1.712	1.820
1,14	100	123	191	293	366	406	469	575	627	665	724	884	1.029	1.201	1.379	1.456

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	123	152	240	368	526	674	871	1.169	1.313	1.406	1.522	1.759	1.856	2.126	2.421	2.597
1,05	122	151	234	365	520	649	802	1.017	1.143	1.218	1.310	1.514	1.660	1.891	2.150	2.302
1,1	121	149	232	364	499	581	682	833	912	964	1.057	1.243	1.436	1.652	1.883	2.002
1,14	119	147	226	341	423	468	538	658	716	759	826	1.008	1.173	1.370	1.572	1.659



VTX 1 M 1030 - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	10,0	8,04	5,00	3,12	2,13	1,63	1,22	0,89	0,79	0,74	0,68	0,59	0,56	0,48	0,43	0,40
1,05	10,0	8,09	5,14	3,16	2,17	1,71	1,38	1,07	0,95	0,89	0,83	0,71	0,65	0,57	0,50	0,47
1,1	10,1	8,18	5,22	3,24	2,33	1,99	1,68	1,37	1,25	1,18	1,07	0,91	0,79	0,69	0,60	0,57
1,14	10,3	8,35	5,38	3,52	2,82	2,53	2,20	1,79	1,64	1,55	1,42	1,16	1,00	0,86	0,75	0,71

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,37	6,80	4,28	2,80	1,96	1,53	1,18	0,88	0,78	0,73	0,68	0,59	0,56	0,48	0,43	0,40
1,05	8,41	6,84	4,40	2,82	1,98	1,59	1,28	1,01	0,90	0,85	0,79	0,68	0,62	0,54	0,48	0,45
1,1	8,50	6,89	4,44	2,83	2,06	1,77	1,51	1,24	1,13	1,07	0,97	0,83	0,72	0,62	0,55	0,51
1,14	8,65	7,02	4,57	3,02	2,44	2,20	1,91	1,57	1,44	1,36	1,25	1,02	0,88	0,75	0,66	0,62