




VTX 1 M 1330 - Cell data sheet

Classification

Brand	Alcad
Cell type	VTX 1 M 1330
Cell P/N	310564081
Capacity at 5 hours rate	1.330 Ah
IEC Designation	KGM1330P
According to IEC 62259	



Wiring principle



Crosswise

Physical data

Overall height	411 mm		
Cell height			
Width	195 mm	Weight per cell	72,0 Kg
Length	522 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	6
Separator type	Felt	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	Low pressure flame arresting vent (large)
Terminal size	M10 SW 16 mm	Handle	Yes

Plates

Positive		Negative	
Type of plates	Maintenance Free Pocket	Type of plates	Maintenance Free Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	17,4 liters		

Connection

Cable area of internal connection cables	70 mm²	End-lug (and external cable)	70 mm²
--	--------	------------------------------	--------



VTX 1 M 1330 - Cell data sheet

Charging

Float voltage	1,42 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,42 V/Cell		

Resistance/Short circuit

Internal resistance	0,09 mOhm	Short circuit current	14420 A
---------------------	-----------	-----------------------	---------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	133	166	266	426	626	817	1.091	1.488	1.682	1.805	1.959	2.271	2.396	2.745	3.126	3.354
1,05	133	164	259	421	614	777	966	1.238	1.398	1.492	1.608	1.862	2.041	2.325	2.645	2.831
1,1	131	163	255	411	571	668	790	973	1.067	1.129	1.240	1.460	1.686	1.940	2.211	2.351
1,14	129	159	247	378	472	525	606	743	810	859	935	1.142	1.329	1.551	1.781	1.880

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	159	196	310	475	679	870	1.125	1.509	1.696	1.815	1.965	2.271	2.396	2.745	3.126	3.354
1,05	158	194	302	471	672	839	1.036	1.313	1.476	1.573	1.692	1.955	2.143	2.441	2.777	2.973
1,1	157	193	300	471	645	750	880	1.076	1.178	1.245	1.366	1.606	1.854	2.134	2.432	2.586
1,14	154	189	291	440	546	604	695	850	925	980	1.066	1.302	1.515	1.768	2.030	2.143



VTX 1 M 1330 - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	10,0	8,04	5,00	3,12	2,13	1,63	1,22	0,89	0,79	0,74	0,68	0,59	0,56	0,48	0,43	0,40
1,05	10,0	8,09	5,14	3,16	2,17	1,71	1,38	1,07	0,95	0,89	0,83	0,71	0,65	0,57	0,50	0,47
1,1	10,1	8,18	5,22	3,24	2,33	1,99	1,68	1,37	1,25	1,18	1,07	0,91	0,79	0,69	0,60	0,57
1,14	10,3	8,35	5,38	3,52	2,82	2,53	2,20	1,79	1,64	1,55	1,42	1,16	1,00	0,86	0,75	0,71

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,37	6,80	4,28	2,80	1,96	1,53	1,18	0,88	0,78	0,73	0,68	0,59	0,56	0,48	0,43	0,40
1,05	8,41	6,84	4,40	2,82	1,98	1,59	1,28	1,01	0,90	0,85	0,79	0,68	0,62	0,54	0,48	0,45
1,1	8,50	6,89	4,44	2,83	2,06	1,77	1,51	1,24	1,13	1,07	0,97	0,83	0,72	0,62	0,55	0,51
1,14	8,65	7,02	4,57	3,02	2,44	2,20	1,91	1,57	1,44	1,36	1,25	1,02	0,88	0,75	0,66	0,62