




VTX 1 M 345 - Cell data sheet

Classification

Brand	Alcad		Wiring principle	Normal
Cell type	VTX 1 M 345			
Cell P/N	310562182			
Capacity at 5 hours rate	345 Ah			
IEC Designation	KGM345P			
According to IEC 62259				

Physical data

Overall height	421 mm		
Cell height			
Width	195 mm	Weight per cell	19,8 Kg
Block length - 2 cells	304 mm	Block length - 3 cells	450 mm

Construction

Container material	Polypropylene	No. of terminals/polarity	2
Separator type	Felt	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	Low pressure flame arresting vent (large)
Terminal size	M10 SW 16 mm	Handle	Yes

Plates

Positive		Negative	
Type of plates	Maintenance Free Pocket	Type of plates	Maintenance Free Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	4,8 liters		

Connection

Cable area of internal connection cables	120 mm ²	End-lug (and external cable)	120 mm ²
--	---------------------	------------------------------	---------------------



VTX 1 M 345 - Cell data sheet

Charging

Float voltage	1,42 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,42 V/Cell		

Resistance/Short circuit

Internal resistance	0,33 mOhm	Short circuit current	3741 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	34,6	42,9	69,0	111	162	212	283	386	436	468	508	589	622	712	811	870
1,05	34,4	42,7	67,1	109	159	201	250	321	363	387	417	483	530	603	686	734
1,1	34,0	42,2	66,1	107	148	173	205	252	277	293	322	379	437	503	573	610
1,14	33,4	41,3	64,1	98,0	123	136	157	193	210	223	242	296	345	402	462	488

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	41,2	50,8	80,5	123	176	226	292	392	440	471	510	589	622	712	811	870
1,05	41,0	50,4	78,3	122	174	218	269	341	383	408	439	507	556	633	720	771
1,1	40,6	50,0	77,7	122	167	195	228	279	306	323	354	416	481	554	631	671
1,14	39,9	49,1	75,6	114	142	157	180	220	240	254	277	338	393	459	527	556



VTX 1 M 345 - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	10,0	8,04	5,00	3,12	2,13	1,63	1,22	0,89	0,79	0,74	0,68	0,59	0,56	0,48	0,43	0,40
1,05	10,0	8,09	5,14	3,16	2,17	1,71	1,38	1,07	0,95	0,89	0,83	0,71	0,65	0,57	0,50	0,47
1,1	10,1	8,18	5,22	3,24	2,33	1,99	1,68	1,37	1,25	1,18	1,07	0,91	0,79	0,69	0,60	0,57
1,14	10,3	8,35	5,38	3,52	2,82	2,53	2,20	1,79	1,64	1,55	1,42	1,16	1,00	0,86	0,75	0,71

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,37	6,80	4,28	2,80	1,96	1,53	1,18	0,88	0,78	0,73	0,68	0,59	0,56	0,48	0,43	0,40
1,05	8,41	6,84	4,40	2,82	1,98	1,59	1,28	1,01	0,90	0,85	0,79	0,68	0,62	0,54	0,48	0,45
1,1	8,50	6,89	4,44	2,83	2,06	1,77	1,51	1,24	1,13	1,07	0,97	0,83	0,72	0,62	0,55	0,51
1,14	8,65	7,02	4,57	3,02	2,44	2,20	1,91	1,57	1,44	1,36	1,25	1,02	0,88	0,75	0,66	0,62