




VTX 1 M 370 - Cell data sheet

Classification

Brand	Alcad		Wiring principle	Normal
Cell type	VTX 1 M 370			
Cell P/N	310562282			
Capacity at 5 hours rate	370 Ah			
IEC Designation	KGM370P			
According to IEC 62259				

Physical data

Overall height	421 mm		
Cell height			
Width	195 mm	Weight per cell	21,4 Kg
Block length - 2 cells	328 mm	Block length - 3 cells	486 mm

Construction

Container material	Polypropylene	No. of terminals/polarity	2
Separator type	Felt	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	Low pressure flame arresting vent (large)
Terminal size	M10 SW 16 mm	Handle	Yes

Plates

Positive		Negative	
Type of plates	Maintenance Free Pocket	Type of plates	Maintenance Free Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	5,3 liters		

Connection

Cable area of internal connection cables	120 mm ²	End-lug (and external cable)	120 mm ²
--	---------------------	------------------------------	---------------------



VTX 1 M 370 - Cell data sheet

Charging

Float voltage	1,42 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,42 V/Cell		

Resistance/Short circuit

Internal resistance	0,31 mOhm	Short circuit current	4012 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	37,1	46,0	74,0	119	174	227	304	414	468	502	545	632	667	764	870	933
1,05	36,9	45,8	72,0	117	171	216	269	345	389	415	447	518	568	647	736	788
1,1	36,5	45,2	70,9	114	159	186	220	271	297	314	345	406	469	540	615	654
1,14	35,8	44,3	68,7	105	131	146	169	207	225	239	260	318	370	432	495	523

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	44,2	54,4	86,4	132	189	242	313	420	472	505	547	632	667	764	870	933
1,05	44,0	54,1	84,0	131	187	233	288	365	411	438	471	544	596	679	772	827
1,1	43,5	53,7	83,4	131	179	209	245	299	328	346	380	447	516	594	677	719
1,14	42,8	52,7	81,0	122	152	168	193	236	257	273	297	362	421	492	565	596



VTX 1 M 370 - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	10,0	8,04	5,00	3,12	2,13	1,63	1,22	0,89	0,79	0,74	0,68	0,59	0,56	0,48	0,43	0,40
1,05	10,0	8,09	5,14	3,16	2,17	1,71	1,38	1,07	0,95	0,89	0,83	0,71	0,65	0,57	0,50	0,47
1,1	10,1	8,18	5,22	3,24	2,33	1,99	1,68	1,37	1,25	1,18	1,07	0,91	0,79	0,69	0,60	0,57
1,14	10,3	8,35	5,38	3,52	2,82	2,53	2,20	1,79	1,64	1,55	1,42	1,16	1,00	0,86	0,75	0,71

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,37	6,80	4,28	2,80	1,96	1,53	1,18	0,88	0,78	0,73	0,68	0,59	0,56	0,48	0,43	0,40
1,05	8,41	6,84	4,40	2,82	1,98	1,59	1,28	1,01	0,90	0,85	0,79	0,68	0,62	0,54	0,48	0,45
1,1	8,50	6,89	4,44	2,83	2,06	1,77	1,51	1,24	1,13	1,07	0,97	0,83	0,72	0,62	0,55	0,51
1,14	8,65	7,02	4,57	3,02	2,44	2,20	1,91	1,57	1,44	1,36	1,25	1,02	0,88	0,75	0,66	0,62