




VTX 1 M 785 - Cell data sheet

Classification

Brand	Alcad
Cell type	VTX 1 M 785
Cell P/N	310563281
Capacity at 5 hours rate	785 Ah
IEC Designation	KGM785P
According to IEC 62259	



Physical data

Overall height	411 mm		
Cell height			
Width	195 mm	Weight per cell	46,0 Kg
Length	352 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	4
Separator type	Felt	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	Low pressure flame arresting vent (large)
Terminal size	M10 SW 16 mm	Handle	Yes

Plates

Positive		Negative	
Type of plates	Maintenance Free Pocket	Type of plates	Maintenance Free Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	11,6 liters		

Connection

Cable area of internal connection cables	70 mm ²	End-lug (and external cable)	70 mm ²
--	--------------------	------------------------------	--------------------

ALCAD confidential and proprietary. The data herein given are for information purposes only and are not binding on ALCAD. They may be modified without prior notice. Please contact an ALCAD representative in order to obtain confirmation of the above data.

Visit our website at www.alcad.com

380603 00000000-0000-0000-0000-000000000000 Version: 3.5, Last updated on 01/2024, Referential data
5/13/2024



VTX 1 M 785 - Cell data sheet

Charging

Float voltage	1,42 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,42 V/Cell		

Resistance/Short circuit

Internal resistance	0,15 mOhm	Short circuit current	8511 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	78,7	97,7	157	251	369	482	644	878	993	1.066	1.156	1.341	1.414	1.620	1.845	1.979
1,05	78,2	97,1	153	249	362	458	570	731	825	881	949	1.099	1.205	1.372	1.561	1.671
1,1	77,4	96,0	150	243	337	394	466	574	630	667	732	862	995	1.145	1.305	1.387
1,14	76,0	94,0	146	223	279	310	358	439	478	507	552	674	784	916	1.051	1.109

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	93,8	115	183	280	401	513	664	891	1.001	1.072	1.160	1.341	1.414	1.620	1.845	1.979
1,05	93,3	115	178	278	396	495	611	775	871	928	999	1.154	1.265	1.441	1.639	1.755
1,1	92,4	114	177	278	380	443	520	635	695	735	806	948	1.094	1.259	1.435	1.526
1,14	90,8	112	172	260	322	357	410	501	546	578	629	768	894	1.044	1.198	1.265

ALCAD confidential and proprietary. The data herein given are for information purposes only and are not binding on ALCAD. They may be modified without prior notice. Please contact an ALCAD representative in order to obtain confirmation of the above data.

Visit our website at www.alcad.com

380603 00000000-0000-0000-0000-000000000000 Version: 3.5, Last updated on 01/2024, Referential data
5/13/2024



VTX 1 M 785 - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	10,0	8,04	5,00	3,12	2,13	1,63	1,22	0,89	0,79	0,74	0,68	0,59	0,56	0,48	0,43	0,40
1,05	10,0	8,09	5,14	3,16	2,17	1,71	1,38	1,07	0,95	0,89	0,83	0,71	0,65	0,57	0,50	0,47
1,1	10,1	8,18	5,22	3,24	2,33	1,99	1,68	1,37	1,25	1,18	1,07	0,91	0,79	0,69	0,60	0,57
1,14	10,3	8,35	5,38	3,52	2,82	2,53	2,20	1,79	1,64	1,55	1,42	1,16	1,00	0,86	0,75	0,71

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,37	6,80	4,28	2,80	1,96	1,53	1,18	0,88	0,78	0,73	0,68	0,59	0,56	0,48	0,43	0,40
1,05	8,41	6,84	4,40	2,82	1,98	1,59	1,28	1,01	0,90	0,85	0,79	0,68	0,62	0,54	0,48	0,45
1,1	8,50	6,89	4,44	2,83	2,06	1,77	1,51	1,24	1,13	1,07	0,97	0,83	0,72	0,62	0,55	0,51
1,14	8,65	7,02	4,57	3,02	2,44	2,20	1,91	1,57	1,44	1,36	1,25	1,02	0,88	0,75	0,66	0,62

ALCAD confidential and proprietary. The data herein given are for information purposes only and are not binding on ALCAD. They may be modified without prior notice. Please contact an ALCAD representative in order to obtain confirmation of the above data.

Visit our website at www.alcad.com