



XHP130 - Cell data sheet


Classification

Brand	Alcad
Cell type	XHP130
Cell P/N	210684
Capacity at 5 hours rate	130 Ah
IEC Designation	KH130P
According to IEC 60623	



Wiring principle

Normal



Physical data

Overall height	339 mm		
Cell height			
Width	166 mm	Weight per cell	7,0 Kg
Length	87 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	1
Separator type	Microporous	Terminal material	Copper
Connection torque	15,0 +/- 2,0 Nm	Vent type	Flame arresting vent
Terminal size	M12		
		Handle	No

Plates

Positive		Negative	
Type of plates	Sintered	Type of plates	Plastic bonded

Electrolyte

Electrolyte type: Renewal		Max/Min	60 mm
Electrolyte type: Initial	E4	Vent oil quantity	
Electrolyte per cell: Liquid	1,5 liters		

Connection

Cable area of internal connection cables	185 mm²	End-lug (and external cable)	185 mm²
--	---------	------------------------------	---------



XHP130 - Cell data sheet

Charging

Float voltage	1,4 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,41 V/Cell		

Resistance/Short circuit

Internal resistance	0,31 mOhm	Short circuit current	4697 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	13,3	16,5	26,0	43,1	64,1	84,9	125	238	332	387	458	542	739	828	1.016	1.092
1,05	13,2	16,4	25,8	42,8	63,7	83,9	124	227	292	332	379	444	628	707	867	942
1,1	13,0	16,2	25,5	41,9	62,0	81,5	117	184	223	251	289	351	510	591	722	778
1,14	12,8	15,9	25,1	40,1	58,8	76,0	102	145	172	195	227	277	425	494	610	670

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes	1.390 A
-------------------	---------

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	16,1	20,0	31,1	51,0	75,6	96,2	136	247	339	393	461	542	739	828	1.016	1.092
1,05	15,9	19,8	30,8	50,7	75,2	96,1	138	245	312	353	400	466	660	742	910	989
1,1	15,7	19,5	30,5	49,6	73,2	94,5	133	205	247	278	319	387	561	650	795	856
1,14	15,5	19,3	30,0	47,6	69,4	88,9	118	167	197	224	259	315	484	564	696	764

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes	1.390 A
-------------------	---------



XHP130 - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,8	7,88	5,00	3,02	2,03	1,53	1,04	0,55	0,39	0,34	0,28	0,24	0,18	0,16	0,13	0,12
1,05	9,9	7,95	5,04	3,04	2,04	1,55	1,05	0,57	0,44	0,39	0,34	0,29	0,21	0,18	0,15	0,14
1,1	10,0	8,05	5,10	3,10	2,10	1,60	1,11	0,71	0,58	0,52	0,45	0,37	0,26	0,22	0,18	0,17
1,14	10,1	8,16	5,18	3,24	2,21	1,71	1,28	0,90	0,75	0,66	0,57	0,47	0,31	0,26	0,21	0,19

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes 1.390 A

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,08	6,51	4,18	2,55	1,72	1,35	0,95	0,53	0,38	0,33	0,28	0,24	0,18	0,16	0,13	0,12
1,05	8,16	6,57	4,22	2,57	1,73	1,35	0,94	0,53	0,42	0,37	0,32	0,28	0,20	0,18	0,14	0,13
1,1	8,26	6,65	4,27	2,62	1,78	1,38	0,98	0,63	0,53	0,47	0,41	0,34	0,23	0,20	0,16	0,15
1,14	8,37	6,74	4,33	2,73	1,87	1,46	1,10	0,78	0,66	0,58	0,50	0,41	0,27	0,23	0,19	0,17

Engine starting performance

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

Available amperes 1.390 A