




XHP80 - Cell data sheet

Classification

Brand	Alcad
Cell type	XHP80
Cell P/N	210680
Capacity at 5 hours rate	80 Ah
IEC Designation	KH80P
According to IEC 60623	



Wiring principle



Crosswise

Physical data

Overall height	306 mm		
Cell height			
Width	86 mm	Weight per cell	3,5 Kg
Length	86 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	1
Separator type	Microporous	Terminal material	Copper
Connection torque	10,0 +/- 2,0 Nm	Vent type	Flame arresting vent
Terminal size	M10 SW 16 mm		
		Handle	No

Plates

Positive		Negative	
Type of plates	Sintered	Type of plates	Plastic bonded

Electrolyte

Electrolyte type: Renewal		Max/Min	70 mm
Electrolyte type: Initial	E4	Vent oil quantity	
Electrolyte per cell: Liquid	0,7 liters		

Connection

Cable area of internal connection cables	70 mm ²	End-lug (and external cable)	70 mm ²
--	--------------------	------------------------------	--------------------



XHP80 - Cell data sheet

Charging

Float voltage	1,4 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,41 V/Cell		

Resistance/Short circuit

Internal resistance	0,50 mOhm	Short circuit current	2548 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,18	10,2	16,0	26,5	39,4	52,2	77,2	149	212	252	300	333	410	449	537	593
1,05	8,11	10,1	15,9	26,3	39,2	51,6	76,2	145	193	223	249	274	343	381	455	497
1,1	8,01	9,9	15,7	25,8	38,2	50,2	72,0	123	153	171	190	216	279	312	376	415
1,14	7,90	9,8	15,4	24,7	36,2	46,8	62,6	104	122	134	150	168	229	259	315	346

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes	905 A
-------------------	-------

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,9	12,3	19,1	31,4	46,6	59,2	83,8	155	217	256	302	333	410	449	537	593
1,05	9,8	12,2	19,0	31,2	46,3	59,2	84,8	157	206	237	263	288	361	400	477	522
1,1	9,7	12,0	18,8	30,5	45,1	58,1	82,0	138	170	189	210	237	307	344	413	456
1,14	9,6	11,9	18,5	29,3	42,7	54,7	72,6	119	140	154	171	192	261	295	359	395

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes	905 A
-------------------	-------



XHP80 - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,8	7,88	5,00	3,02	2,03	1,53	1,04	0,54	0,38	0,32	0,27	0,24	0,20	0,18	0,15	0,14
1,05	9,9	7,95	5,04	3,04	2,04	1,55	1,05	0,55	0,42	0,36	0,32	0,29	0,23	0,21	0,18	0,16
1,1	10,0	8,05	5,10	3,10	2,10	1,60	1,11	0,65	0,52	0,47	0,42	0,37	0,29	0,26	0,21	0,19
1,14	10,1	8,16	5,18	3,24	2,21	1,71	1,28	0,77	0,66	0,60	0,53	0,48	0,35	0,31	0,25	0,23

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes 905 A

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,08	6,51	4,18	2,55	1,72	1,35	0,95	0,52	0,37	0,31	0,26	0,24	0,20	0,18	0,15	0,14
1,05	8,16	6,57	4,22	2,57	1,73	1,35	0,94	0,51	0,39	0,34	0,30	0,28	0,22	0,20	0,17	0,15
1,1	8,26	6,65	4,27	2,62	1,78	1,38	0,98	0,58	0,47	0,42	0,38	0,34	0,26	0,23	0,19	0,18
1,14	8,37	6,74	4,33	2,73	1,87	1,46	1,10	0,67	0,57	0,52	0,47	0,42	0,31	0,27	0,22	0,20

Engine starting performance

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

Available amperes 905 A