



HB230P - Cell data sheet

Classification


Brand
Cell type
Cell P/N
Capacity at 5 hours rate
IEC Designation
According to IEC 60623

HB230P
310051481
230 Ah
KH230P



Wiring principle

Crosswise



Physical data

Overall height	410 mm		
Cell height	400 mm		
Width	195 mm	Weight per cell	20,8 Kg
Length	159 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	2
Separator type	Grid	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	
Terminal size	M10 SW 16 mm		
		Handle	Yes

Plates

Positive		Negative	
Type of plates	Pocket	Type of plates	Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	5,9 liters		

Connection

Cable area of internal connection cables	120 mm ²	End-lug (and external cable)	120 mm ²
--	---------------------	------------------------------	---------------------



HB230P - Cell data sheet

Charging

Float voltage	1,4 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,43 V/Cell		

Resistance/Short circuit

Internal resistance	0,19 mOhm	Short circuit current	6840 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	23,0	28,8	46,0	75,9	112	148	217	393	529	606	716	868	1.090	1.230	1.495	1.591
1,05	22,8	28,6	45,4	74,7	110	145	210	373	453	516	606	706	915	1.032	1.245	1.298
1,1	22,2	27,8	44,4	72,7	107	140	198	303	356	400	450	543	729	829	987	1.037
1,14	21,6	27,1	42,6	69,6	98,0	124	163	239	285	320	362	443	581	666	784	812
1,16	21,0	26,2	41,6	66,9	89,9	111	132	198	237	263	291	364	494	557	652	690

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes	2.008 A
-------------------	---------

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	27,9	34,9	55,0	90,0	133	168	235	409	541	615	721	868	1.090	1.230	1.495	1.591
1,05	27,6	34,6	54,2	88,5	130	166	233	403	484	547	640	741	960	1.084	1.308	1.363
1,1	26,9	33,6	53,0	86,1	126	162	226	339	395	443	497	597	802	913	1.086	1.141
1,14	26,2	32,7	50,9	82,5	116	145	189	275	326	366	414	505	663	760	894	926
1,16	25,4	31,7	49,7	79,3	106	130	155	231	275	305	338	422	573	646	757	801

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes	2.008 A
-------------------	---------



HB230P - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	10,0	7,98	5,00	3,03	2,04	1,55	1,06	0,58	0,44	0,38	0,32	0,26	0,21	0,19	0,15	0,14
1,05	10,1	8,05	5,07	3,08	2,08	1,59	1,10	0,62	0,51	0,45	0,38	0,33	0,25	0,22	0,18	0,18
1,1	10,3	8,27	5,19	3,17	2,15	1,65	1,16	0,76	0,65	0,58	0,51	0,42	0,32	0,28	0,23	0,22
1,14	10,6	8,50	5,40	3,30	2,35	1,85	1,41	0,96	0,81	0,72	0,64	0,52	0,40	0,35	0,29	0,28
1,16	11,0	8,77	5,53	3,44	2,56	2,07	1,74	1,16	0,97	0,88	0,79	0,63	0,47	0,41	0,35	0,33

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes 2.008 A

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,25	6,60	4,18	2,56	1,73	1,37	0,98	0,56	0,43	0,37	0,32	0,26	0,21	0,19	0,15	0,14
1,05	8,32	6,66	4,24	2,60	1,76	1,39	0,99	0,57	0,48	0,42	0,36	0,31	0,24	0,21	0,18	0,17
1,1	8,54	6,83	4,34	2,67	1,83	1,42	1,02	0,68	0,58	0,52	0,46	0,38	0,29	0,25	0,21	0,20
1,14	8,78	7,02	4,52	2,79	1,99	1,58	1,22	0,84	0,70	0,63	0,56	0,46	0,35	0,30	0,26	0,25
1,16	9,06	7,25	4,63	2,90	2,17	1,77	1,49	1,00	0,84	0,75	0,68	0,54	0,40	0,36	0,30	0,29

Engine starting performance

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

Available amperes 2.008 A