




HB440P - Cell data sheet

Classification

Brand	
Cell type	HB440P
Cell P/N	311027481
Capacity at 5 hours rate	440 Ah
IEC Designation	KH440P
According to IEC 60623	



Wiring principle



Crosswise

Physical data

Overall height	410 mm		
Cell height	400 mm		
Width	195 mm	Weight per cell	37,4 Kg
Length	268 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	3
Separator type	Grid	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	
Terminal size	M10 SW 16 mm		
		Handle	Yes

Plates

Positive		Negative	
Type of plates	Pocket	Type of plates	Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	9,9 liters		

Connection

Cable area of internal connection cables	120 mm ²	End-lug (and external cable)	120 mm ²
--	---------------------	------------------------------	---------------------



HB440P - Cell data sheet

Charging

Float voltage	1,4 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,43 V/Cell		

Resistance/Short circuit

Internal resistance	0,10 mOhm	Short circuit current	13084 A
---------------------	-----------	-----------------------	---------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	44,1	55,1	88,0	145	215	283	415	753	1.011	1.159	1.369	1.661	2.085	2.353	2.861	3.043
1,05	43,7	54,6	86,8	143	211	277	401	714	868	986	1.160	1.350	1.750	1.975	2.382	2.483
1,1	42,6	53,2	84,8	139	204	267	380	580	680	765	862	1.039	1.395	1.587	1.888	1.985
1,14	41,4	51,8	81,5	133	187	238	312	458	545	612	693	848	1.112	1.275	1.500	1.553
1,16	40,1	50,2	79,5	128	172	212	253	379	453	502	557	697	944	1.065	1.248	1.321

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes 3.842 A

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	53,4	66,7	105	172	254	321	450	782	1.035	1.177	1.380	1.661	2.085	2.353	2.861	3.043
1,05	52,9	66,1	104	169	249	318	446	770	926	1.047	1.225	1.418	1.837	2.074	2.501	2.608
1,1	51,5	64,4	101	165	241	309	432	648	755	847	951	1.143	1.534	1.746	2.077	2.184
1,14	50,1	62,6	97,4	158	221	278	362	526	625	700	791	966	1.268	1.454	1.711	1.771
1,16	48,6	60,7	95,0	152	203	249	296	442	526	584	647	808	1.096	1.236	1.448	1.532

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes 3.842 A



HB440P - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	10,0	7,98	5,00	3,03	2,04	1,55	1,06	0,58	0,44	0,38	0,32	0,26	0,21	0,19	0,15	0,14
1,05	10,1	8,05	5,07	3,08	2,08	1,59	1,10	0,62	0,51	0,45	0,38	0,33	0,25	0,22	0,18	0,18
1,1	10,3	8,27	5,19	3,17	2,15	1,65	1,16	0,76	0,65	0,58	0,51	0,42	0,32	0,28	0,23	0,22
1,14	10,6	8,50	5,40	3,30	2,35	1,85	1,41	0,96	0,81	0,72	0,64	0,52	0,40	0,35	0,29	0,28
1,16	11,0	8,77	5,53	3,44	2,56	2,07	1,74	1,16	0,97	0,88	0,79	0,63	0,47	0,41	0,35	0,33

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes 3.842 A

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,25	6,60	4,18	2,56	1,73	1,37	0,98	0,56	0,43	0,37	0,32	0,26	0,21	0,19	0,15	0,14
1,05	8,32	6,66	4,24	2,60	1,76	1,39	0,99	0,57	0,48	0,42	0,36	0,31	0,24	0,21	0,18	0,17
1,1	8,54	6,83	4,34	2,67	1,83	1,42	1,02	0,68	0,58	0,52	0,46	0,38	0,29	0,25	0,21	0,20
1,14	8,78	7,02	4,52	2,79	1,99	1,58	1,22	0,84	0,70	0,63	0,56	0,46	0,35	0,30	0,26	0,25
1,16	9,06	7,25	4,63	2,90	2,17	1,77	1,49	1,00	0,84	0,75	0,68	0,54	0,40	0,36	0,30	0,29

Engine starting performance

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

Available amperes 3.842 A