




HB615P - Cell data sheet

Classification

Brand	
Cell type	HB615P
Cell P/N	310101081
Capacity at 5 hours rate	615 Ah
IEC Designation	KH615P
According to IEC 60623	



Wiring principle



Crosswise

Physical data

Overall height	410 mm		
Cell height	400 mm		
Width	195 mm	Weight per cell	51,0 Kg
Length	353 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	4
Separator type	Grid	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	
Terminal size	M10 SW 16 mm		
		Handle	Yes

Plates

Positive		Negative	
Type of plates	Pocket	Type of plates	Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	12,8 liters		

Connection

Cable area of internal connection cables	120 mm²	End-lug (and external cable)	120 mm²
--	---------	------------------------------	---------



HB615P - Cell data sheet

Charging

Float voltage	1,4 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,43 V/Cell		

Resistance/Short circuit

Internal resistance	0,07 mOhm	Short circuit current	18288 A
---------------------	-----------	-----------------------	---------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	61,6	77,0	123	203	301	396	579	1.052	1.413	1.620	1.914	2.322	2.915	3.289	3.999	4.253
1,05	61,1	76,4	121	200	295	387	561	998	1.213	1.379	1.621	1.886	2.445	2.760	3.330	3.471
1,1	59,5	74,4	119	194	285	373	531	811	951	1.069	1.204	1.452	1.949	2.218	2.639	2.774
1,14	57,9	72,4	114	186	262	332	436	640	762	855	968	1.185	1.554	1.782	2.097	2.171
1,16	56,1	70,1	111	179	240	296	354	530	633	702	779	974	1.320	1.489	1.744	1.846

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes 5.370 A

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	74,6	93,2	147	241	355	449	629	1.093	1.447	1.646	1.929	2.322	2.915	3.289	3.999	4.253
1,05	73,9	92,4	145	237	349	444	624	1.076	1.294	1.463	1.712	1.981	2.568	2.900	3.496	3.646
1,1	72,0	90,0	142	230	337	433	604	906	1.056	1.184	1.329	1.597	2.144	2.440	2.904	3.052
1,14	70,0	87,6	136	221	309	389	505	735	873	978	1.106	1.351	1.772	2.032	2.391	2.475
1,16	67,9	84,9	133	212	284	348	414	617	735	816	904	1.129	1.531	1.728	2.024	2.141

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes 5.370 A



HB615P - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	10,0	7,98	5,00	3,03	2,04	1,55	1,06	0,58	0,44	0,38	0,32	0,26	0,21	0,19	0,15	0,14
1,05	10,1	8,05	5,07	3,08	2,08	1,59	1,10	0,62	0,51	0,45	0,38	0,33	0,25	0,22	0,18	0,18
1,1	10,3	8,27	5,19	3,17	2,15	1,65	1,16	0,76	0,65	0,58	0,51	0,42	0,32	0,28	0,23	0,22
1,14	10,6	8,50	5,40	3,30	2,35	1,85	1,41	0,96	0,81	0,72	0,64	0,52	0,40	0,35	0,29	0,28
1,16	11,0	8,77	5,53	3,44	2,56	2,07	1,74	1,16	0,97	0,88	0,79	0,63	0,47	0,41	0,35	0,33

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes 5.370 A

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,25	6,60	4,18	2,56	1,73	1,37	0,98	0,56	0,43	0,37	0,32	0,26	0,21	0,19	0,15	0,14
1,05	8,32	6,66	4,24	2,60	1,76	1,39	0,99	0,57	0,48	0,42	0,36	0,31	0,24	0,21	0,18	0,17
1,1	8,54	6,83	4,34	2,67	1,83	1,42	1,02	0,68	0,58	0,52	0,46	0,38	0,29	0,25	0,21	0,20
1,14	8,78	7,02	4,52	2,79	1,99	1,58	1,22	0,84	0,70	0,63	0,56	0,46	0,35	0,30	0,26	0,25
1,16	9,06	7,25	4,63	2,90	2,17	1,77	1,49	1,00	0,84	0,75	0,68	0,54	0,40	0,36	0,30	0,29

Engine starting performance

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

Available amperes 5.370 A