



HC145P - Cell data sheet

Classification


Brand
Cell type
Cell P/N
Capacity at 5 hours rate
IEC Designation
According to IEC 60623

HC145P
310452451
145 Ah
KH145P



Wiring principle

Normal



Physical data

Overall height	413 mm		
Cell height	405 mm		
Width	192 mm	Weight per cell	13,0 Kg
Length	93 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	1
Separator type	Grid	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	
Terminal size	M10 SW 16 mm		
		Handle	No

Plates

Positive		Negative	
Type of plates	Pocket	Type of plates	Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	3,7 liters		

Connection

Cable area of internal connection cables	120 mm²	End-lug (and external cable)	120 mm²
--	---------	------------------------------	---------



HC145P - Cell data sheet

Charging

Float voltage	1,4 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,43 V/Cell		

Resistance/Short circuit

Internal resistance	0,30 mOhm	Short circuit current	4312 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	14,5	18,2	29,0	47,9	70,9	93,4	137	248	333	382	451	547	687	775	943	1.003
1,05	14,4	18,0	28,6	47,1	69,7	91,3	132	235	286	325	382	445	577	651	785	818
1,1	14,0	17,5	28,0	45,8	67,3	88,0	125	191	224	252	284	342	460	523	622	654
1,14	13,6	17,1	26,8	43,9	61,8	78,4	103	151	180	202	228	279	366	420	494	512
1,16	13,2	16,5	26,2	42,2	56,7	69,9	83,4	125	149	166	184	230	311	351	411	435

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes	1.266 A
-------------------	---------

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	17,6	22,0	34,7	56,7	83,7	106	148	258	341	388	455	547	687	775	943	1.003
1,05	17,4	21,8	34,2	55,8	82,2	105	147	254	305	345	404	467	605	684	824	860
1,1	17,0	21,2	33,4	54,3	79,4	102	142	214	249	279	313	377	506	575	685	720
1,14	16,5	20,6	32,1	52,0	72,9	91,7	119	173	206	231	261	318	418	479	564	584
1,16	16,0	20,0	31,3	50,0	66,9	82,1	97,5	146	173	192	213	266	361	407	477	505

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes	1.266 A
-------------------	---------



HC145P - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	10,0	7,98	5,00	3,03	2,04	1,55	1,06	0,58	0,44	0,38	0,32	0,26	0,21	0,19	0,15	0,14
1,05	10,1	8,05	5,07	3,08	2,08	1,59	1,10	0,62	0,51	0,45	0,38	0,33	0,25	0,22	0,18	0,18
1,1	10,3	8,27	5,19	3,17	2,15	1,65	1,16	0,76	0,65	0,58	0,51	0,42	0,32	0,28	0,23	0,22
1,14	10,6	8,50	5,40	3,30	2,35	1,85	1,41	0,96	0,81	0,72	0,64	0,52	0,40	0,35	0,29	0,28
1,16	11,0	8,77	5,53	3,44	2,56	2,07	1,74	1,16	0,97	0,88	0,79	0,63	0,47	0,41	0,35	0,33

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes 1.266 A

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,25	6,60	4,18	2,56	1,73	1,37	0,98	0,56	0,43	0,37	0,32	0,26	0,21	0,19	0,15	0,14
1,05	8,32	6,66	4,24	2,60	1,76	1,39	0,99	0,57	0,48	0,42	0,36	0,31	0,24	0,21	0,18	0,17
1,1	8,54	6,83	4,34	2,67	1,83	1,42	1,02	0,68	0,58	0,52	0,46	0,38	0,29	0,25	0,21	0,20
1,14	8,78	7,02	4,52	2,79	1,99	1,58	1,22	0,84	0,70	0,63	0,56	0,46	0,35	0,30	0,26	0,25
1,16	9,06	7,25	4,63	2,90	2,17	1,77	1,49	1,00	0,84	0,75	0,68	0,54	0,40	0,36	0,30	0,29

Engine starting performance

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

Available amperes 1.266 A