




HC185P - Cell data sheet

Classification

Brand			Wiring principle	Normal
Cell type	HC185P			
Cell P/N	310452651			
Capacity at 5 hours rate	185 Ah			
IEC Designation	KH185P			
According to IEC 60623				



Physical data

Overall height	413 mm		
Cell height	405 mm		
Width	196 mm	Weight per cell	17,2 Kg
Length	126 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	2
Separator type	Grid	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	
Terminal size	M10 SW 16 mm		
		Handle	No

Plates

Positive		Negative	
Type of plates	Pocket	Type of plates	Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	5,0 liters		

Connection

Cable area of internal connection cables	95 mm ²	End-lug (and external cable)	95 mm ²
--	--------------------	------------------------------	--------------------



HC185P - Cell data sheet

Charging

Float voltage	1,4 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,43 V/Cell		

Resistance/Short circuit

Internal resistance	0,23 mOhm	Short circuit current	5501 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	18,5	23,2	37,0	61,1	90,5	119	174	316	425	487	576	698	877	989	1.203	1.279
1,05	18,4	23,0	36,5	60,1	88,9	116	169	300	365	415	488	567	736	830	1.002	1.044
1,1	17,9	22,4	35,7	58,4	85,8	112	160	244	286	322	362	437	586	667	794	834
1,14	17,4	21,8	34,3	56,0	78,8	100	131	193	229	257	291	356	468	536	631	653
1,16	16,9	21,1	33,4	53,8	72,3	89,2	106	159	190	211	234	293	397	448	525	555

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes	1.615 A
-------------------	---------

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	22,4	28,0	44,2	72,4	107	135	189	329	435	495	580	698	877	989	1.203	1.279
1,05	22,2	27,8	43,6	71,2	105	134	188	324	389	440	515	596	772	872	1.052	1.097
1,1	21,6	27,1	42,6	69,2	101	130	182	272	318	356	400	481	645	734	873	918
1,14	21,1	26,3	40,9	66,4	93,0	117	152	221	263	294	333	406	533	611	719	744
1,16	20,4	25,5	39,9	63,8	85,4	105	124	186	221	245	272	340	461	520	609	644

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes	1.615 A
-------------------	---------



HC185P - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	10,0	7,98	5,00	3,03	2,04	1,55	1,06	0,58	0,44	0,38	0,32	0,26	0,21	0,19	0,15	0,14
1,05	10,1	8,05	5,07	3,08	2,08	1,59	1,10	0,62	0,51	0,45	0,38	0,33	0,25	0,22	0,18	0,18
1,1	10,3	8,27	5,19	3,17	2,15	1,65	1,16	0,76	0,65	0,58	0,51	0,42	0,32	0,28	0,23	0,22
1,14	10,6	8,50	5,40	3,30	2,35	1,85	1,41	0,96	0,81	0,72	0,64	0,52	0,40	0,35	0,29	0,28
1,16	11,0	8,77	5,53	3,44	2,56	2,07	1,74	1,16	0,97	0,88	0,79	0,63	0,47	0,41	0,35	0,33

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes 1.615 A

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,25	6,60	4,18	2,56	1,73	1,37	0,98	0,56	0,43	0,37	0,32	0,26	0,21	0,19	0,15	0,14
1,05	8,32	6,66	4,24	2,60	1,76	1,39	0,99	0,57	0,48	0,42	0,36	0,31	0,24	0,21	0,18	0,17
1,1	8,54	6,83	4,34	2,67	1,83	1,42	1,02	0,68	0,58	0,52	0,46	0,38	0,29	0,25	0,21	0,20
1,14	8,78	7,02	4,52	2,79	1,99	1,58	1,22	0,84	0,70	0,63	0,56	0,46	0,35	0,30	0,26	0,25
1,16	9,06	7,25	4,63	2,90	2,17	1,77	1,49	1,00	0,84	0,75	0,68	0,54	0,40	0,36	0,30	0,29

Engine starting performance

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

Available amperes 1.615 A