




HC80P - Cell data sheet

Classification

Brand	
Cell type	HC80P
Cell P/N	310451851
Capacity at 5 hours rate	80 Ah
IEC Designation	KH80P
According to	IEC 60623



Wiring principle Normal



Physical data

Overall height	357 mm		
Cell height	349 mm		
Width	192 mm	Weight per cell	8,1 Kg
Length	68 mm		

Construction

Container material	Polypropylene	No. of terminals/polarity	1
Separator type	Grid	Terminal material	Steel
Connection torque	30,0 +/- 3,0 Nm	Vent type	
Terminal size	M10 SW 16 mm	Handle	No

Plates

Positive		Negative	
Type of plates	Pocket	Type of plates	Pocket

Electrolyte

Electrolyte type: Renewal	E13	Max/Min	50 mm
Electrolyte type: Initial	E22	Vent oil quantity	
Electrolyte per cell: Liquid	2,2 liters		

Connection

Cable area of internal connection cables	95 mm ²	End-lug (and external cable)	95 mm ²
--	--------------------	------------------------------	--------------------



HC80P - Cell data sheet

Charging

Float voltage	1,4 V/Cell	High rate voltage (min)	1,45 V/Cell
Single-level voltage	1,43 V/Cell		

Resistance/Short circuit

Internal resistance	0,49 mOhm	Short circuit current	2797 A
---------------------	-----------	-----------------------	--------

Performance data

Current discharge

After prolonged float charge of fully charged cells. Available amperes at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,03	10,0	16,0	26,3	39,0	51,4	75,2	138	185	216	257	318	412	470	593	650
1,05	7,97	10,0	15,8	26,0	38,3	50,3	72,6	131	160	185	219	259	351	400	494	530
1,1	7,77	9,7	15,4	25,2	37,1	48,5	68,9	107	128	144	163	201	277	320	392	439
1,14	7,51	9,39	14,8	24,2	35,4	45,9	60,9	83,3	99,1	111	126	154	221	256	320	336
1,16	7,30	9,12	14,4	23,3	32,5	40,9	49,4	68,4	83,3	90,7	101	127	188	214	266	287

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes	761 A
-------------------	-------

Power discharge

Available power (W), after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	9,7	12,2	19,1	31,2	46,0	58,3	81,7	143	190	219	259	318	412	470	593	650
1,05	9,6	12,0	18,8	30,8	45,2	57,6	80,8	141	171	196	231	272	369	420	519	556
1,1	9,40	11,8	18,3	29,9	43,7	56,2	78,5	119	142	160	180	221	304	352	431	483
1,14	9,09	11,4	17,7	28,7	41,8	53,7	70,6	95,7	114	127	144	176	252	292	365	384
1,16	8,83	11,0	17,2	27,6	38,4	48,1	57,8	79,7	96,9	105	117	147	218	249	309	333

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes	761 A
-------------------	-------



HC80P - Cell data sheet

Kt Factor

Current discharge

After prolonged float charge of fully charged cells. Kt factor at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	10,0	7,97	5,00	3,04	2,05	1,56	1,06	0,58	0,43	0,37	0,31	0,25	0,19	0,17	0,14	0,12
1,05	10,0	8,03	5,08	3,08	2,09	1,59	1,10	0,61	0,50	0,43	0,37	0,31	0,23	0,20	0,16	0,15
1,1	10,3	8,24	5,21	3,17	2,16	1,65	1,16	0,75	0,63	0,55	0,49	0,40	0,29	0,25	0,20	0,18
1,14	10,7	8,52	5,41	3,30	2,26	1,74	1,31	0,96	0,81	0,72	0,64	0,52	0,36	0,31	0,25	0,24
1,16	11,0	8,77	5,55	3,44	2,46	1,96	1,62	1,17	0,96	0,88	0,79	0,63	0,43	0,37	0,30	0,28

Engine starting performance

For a fully charged cell by a constant current charge according to IEC 60623 standard at +20°C +/- 5°C (+68°F +/- 9°F), 30 seconds discharge down to 0,85 V

Available amperes 761 A

Power discharge

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

V/Cell	10h	8h	5h	3h	2h	1,5h	1h	30m	20m	15m	10m	5m	1m	30s	5s	1s
1	8,23	6,58	4,18	2,57	1,74	1,37	0,98	0,56	0,42	0,36	0,31	0,25	0,19	0,17	0,14	0,12
1,05	8,30	6,64	4,25	2,60	1,77	1,39	0,99	0,57	0,47	0,41	0,35	0,29	0,22	0,19	0,15	0,14
1,1	8,51	6,81	4,36	2,68	1,83	1,42	1,02	0,67	0,56	0,50	0,44	0,36	0,26	0,23	0,19	0,17
1,14	8,80	7,04	4,53	2,78	1,91	1,49	1,13	0,84	0,70	0,63	0,56	0,46	0,32	0,27	0,22	0,21
1,16	9,06	7,25	4,64	2,90	2,08	1,66	1,38	1,00	0,83	0,76	0,68	0,54	0,37	0,32	0,26	0,24

Engine starting performance

Kt factor power, after prolonged float charged of fully charged cells at +20°C +/- 5°C (+68°F +/- 9°F)

Available amperes 761 A